

IRF1010NPbF


HEXFET® Power MOSFET

- Advanced Process Technology
- Ultra Low On-Resistance
- Dynamic dv/dt Rating
- 175°C Operating Temperature
- Fast Switching
- Fully Avalanche Rated
- Lead-Free


Description

Advanced HEXFET® Power MOSFETs from International Rectifier utilize advanced processing techniques to achieve extremely low on-resistance per silicon area. This benefit, combined with the fast switching speed and ruggedized device design that HEXFET power MOSFETs are well known for, provides the designer with an extremely efficient and reliable device for use in a wide variety of applications.

The TO-220 package is universally preferred for all commercial-industrial applications at power dissipation levels to approximately 50 watts. The low thermal resistance and low package cost of the TO-220 contribute to its wide acceptance throughout the industry.



$V_{DSS} = 55V$
 $R_{DS(on)} = 11m\Omega$
 $I_D = 85A\text{ (at }V_{GS}=10V)$



Absolute Maximum Ratings

| | Parameter | Max. | Units |
|---------------------------|--|------------------------|---------------|
| $I_D @ T_C = 25^\circ C$ | Continuous Drain Current, $V_{GS} @ 10V$ | 85A | A |
| $I_D @ T_C = 100^\circ C$ | Continuous Drain Current, $V_{GS} @ 10V$ | 60 | |
| I_{DM} | Pulsed Drain Current ① | 290 | |
| $P_D @ T_C = 25^\circ C$ | Power Dissipation | 180 | W |
| | Linear Derating Factor | 1.2 | W/ $^\circ C$ |
| V_{GS} | Gate-to-Source Voltage | ± 20 | V |
| I_{AR} | Avalanche Current ① | 43 | A |
| E_{AR} | Repetitive Avalanche Energy ① | 18 | mJ |
| dv/dt | Peak Diode Recovery dv/dt ③ | 3.6 | V/ns |
| T_J | Operating Junction and | -55 to + 175 | $^\circ C$ |
| T_{STG} | Storage Temperature Range | | |
| | Soldering Temperature, for 10 seconds | | |
| | Mounting torque, 6-32 or M3 screw | 300 (1.6mm from case) | |
| | | 10 lbf•in (1.1N•m) | |

Thermal Resistance

| | Parameter | Typ. | Max. | Units |
|-----------------|-------------------------------------|------|------|--------------|
| $R_{\theta JC}$ | Junction-to-Case | — | 0.85 | $^\circ C/W$ |
| $R_{\theta CS}$ | Case-to-Sink, Flat, Greased Surface | 0.50 | — | |
| $R_{\theta JA}$ | Junction-to-Ambient | — | 62 | |



IRF1010NPbF

KERSEMI

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|---|--------------------------------------|------|--------------|-------------|--|--|
| $V_{(\text{BR})\text{DSS}}$ | Drain-to-Source Breakdown Voltage | 55 | — | — | V | $V_{\text{GS}} = 0\text{V}$, $I_D = 250\mu\text{A}$ |
| $\Delta V_{(\text{BR})\text{DSS}/\Delta T_J}$ | Breakdown Voltage Temp. Coefficient | — | 0.058 | — | V°C | Reference to 25°C , $I_D = 1\text{mA}$ |
| $R_{\text{DS}(\text{on})}$ | Static Drain-to-Source On-Resistance | — | — | 11 | $\text{m}\Omega$ | $V_{\text{GS}} = 10\text{V}$, $I_D = 43\text{A}$ ④ |
| $V_{\text{GS}(\text{th})}$ | Gate Threshold Voltage | 2.0 | — | 4.0 | V | $V_{\text{DS}} = V_{\text{GS}}$, $I_D = 250\mu\text{A}$ |
| g_{fs} | Forward Transconductance | 32 | — | — | S | $V_{\text{DS}} = 25\text{V}$, $I_D = 43\text{A}$ ④ |
| I_{DSS} | Drain-to-Source Leakage Current | — | — | 25 | μA | $V_{\text{DS}} = 55\text{V}$, $V_{\text{GS}} = 0\text{V}$ |
| | | — | — | 250 | | $V_{\text{DS}} = 44\text{V}$, $V_{\text{GS}} = 0\text{V}$, $T_J = 150^\circ\text{C}$ |
| I_{GSS} | Gate-to-Source Forward Leakage | — | — | 100 | nA | $V_{\text{GS}} = 20\text{V}$ |
| | Gate-to-Source Reverse Leakage | — | — | -100 | | $V_{\text{GS}} = -20\text{V}$ |
| Q_g | Total Gate Charge | — | — | 120 | nC | $I_D = 43\text{A}$ |
| Q_{gs} | Gate-to-Source Charge | — | — | 19 | | $V_{\text{DS}} = 44\text{V}$ |
| Q_{gd} | Gate-to-Drain ("Miller") Charge | — | — | 41 | | $V_{\text{GS}} = 10\text{V}$, See Fig. 6 and 13 |
| $t_{\text{d}(\text{on})}$ | Turn-On Delay Time | — | 13 | — | ns | $V_{\text{DD}} = 28\text{V}$ |
| t_r | Rise Time | — | 76 | — | | $I_D = 43\text{A}$ |
| $t_{\text{d}(\text{off})}$ | Turn-Off Delay Time | — | 39 | — | | $R_G = 3.6\Omega$ |
| t_f | Fall Time | — | 48 | — | | $V_{\text{GS}} = 10\text{V}$, See Fig. 10 ④ |
| L_D | Internal Drain Inductance | — | 4.5 | — | nH | Between lead, 6mm (0.25in.) from package and center of die contact |
| L_S | Internal Source Inductance | — | 7.5 | — | | |
| C_{iss} | Input Capacitance | — | 3210 | — | pF | $V_{\text{GS}} = 0\text{V}$ |
| C_{oss} | Output Capacitance | — | 690 | — | | $V_{\text{DS}} = 25\text{V}$ |
| C_{rss} | Reverse Transfer Capacitance | — | 140 | — | | $f = 1.0\text{MHz}$, See Fig. 5 |
| E_{AS} | Single Pulse Avalanche Energy ② | — | 1030 ③ 250 ⑥ | mJ | $I_{\text{AS}} = 4.3\text{A}$, $L = 270\mu\text{H}$ | |

Source-Drain Ratings and Characteristics

| | Parameter | Min. | Typ. | Max. | Units | Conditions |
|-----------------|---|---|------|------|-------------|---|
| I_S | Continuous Source Current (Body Diode) | — | — | 85 ⑦ | A | MOSFET symbol showing the integral reverse p-n junction diode. |
| I_{SM} | Pulsed Source Current (Body Diode) ① | — | — | 290 | | |
| V_{SD} | Diode Forward Voltage | — | — | 1.3 | V | $T_J = 25^\circ\text{C}$, $I_S = 43\text{A}$, $V_{\text{GS}} = 0\text{V}$ ④ |
| t_{rr} | Reverse Recovery Time | — | 69 | 100 | ns | $T_J = 25^\circ\text{C}$, $I_F = 43\text{A}$ |
| Q_{rr} | Reverse Recovery Charge | — | 220 | 230 | nC | $dI/dt = 100\text{A}/\mu\text{s}$ ④ |
| t_{on} | Forward Turn-On Time | Intrinsic turn-on time is negligible (turn-on is dominated by $L_S + L_D$) | | | | |

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature. (See fig. 11)
- ② Starting $T_J = 25^\circ\text{C}$, $L = 270\mu\text{H}$
 $R_G = 25\Omega$, $I_{\text{AS}} = 43\text{A}$, $V_{\text{GS}}=10\text{V}$ (See Figure 12)
- ③ $I_{\text{SD}} \leq 43\text{A}$, $di/dt \leq 210\text{A}/\mu\text{s}$, $V_{\text{DD}} \leq V_{(\text{BR})\text{DSS}}$, $T_J \leq 175^\circ\text{C}$
- ④ Pulse width $\leq 400\mu\text{s}$; duty cycle $\leq 2\%$.
- ⑤ This is a typical value at device destruction and represents operation outside rated limits.
- ⑥ This is a calculated value limited to $T_J = 175^\circ\text{C}$.
- ⑦ Calculated continuous current based on maximum allowable junction temperature. Package limitation current is 75A.




Fig 1. Typical Output Characteristics




Fig 2. Typical Output Characteristics




Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance Vs. Temperature



IRF1010NPbF




Fig 5. Typical Capacitance Vs.
Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs.
Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode
Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 9. Maximum Drain Current Vs.
Case Temperature




Fig 10a. Switching Time Test Circuit




Fig 10b. Switching Time Waveforms




Fig 11. Maximum Effective Transient Thermal Impedance, Junction-to-Case

IRF1010NPbF




Fig 12a. Unclamped Inductive Test Circuit




Fig 12b. Unclamped Inductive Waveforms




Fig 12c. Maximum Avalanche Energy Vs. Drain Current




Fig 13a. Basic Gate Charge Waveform





Fig 13b. Gate Charge Test Circuit




KERSEMI

IRF1010NPbF

Peak Diode Recovery dv/dt Test Circuit



* Reverse Polarity of D.U.T for P-Channel



*** $V_{GS} = 5.0V$ for Logic Level and 3V Drive Devices

Fig 14. For N-channel HEXFET® power MOSFETs




IRF1010NPbF

KERSEMI

TO-220AB Package Outline

Dimensions are shown in millimeters (inches)



NOTES:

1 DIMENSIONING & TOLERANCING PER ANSI Y14.5M, 1982.

2 CONTROLLING DIMENSION : INCH

3 OUTLINE CONFORMS TO JEDEC OUTLINE TO-220AB.

4 HEATSINK & LEAD MEASUREMENTS DO NOT INCLUDE BURRS.

TO-220AB Part Marking Information

EXAMPLE: THIS IS AN IRF1010
 LOT CODE 1789
 ASSEMBLED ON WW 19, 1997
 IN THE ASSEMBLY LINE "C"
Note: "P" in assembly line position indicates "Lead-Free"

