

Part/Keyword Search



Detailed Drawing



Printer Friendly
Datasheet

RN7370 / SRN7370*


* Part number for additional environmental screening.

Performance Data


Frequency	20.0 - 250.0 MHz
Gain	8.5 dB Typical 7.3 dB Min
Noise Figure	1.9 dB Typical 3.4 dB Max
P _{1dB}	23.0 dBm Typical 20.0 dBm Min
3 rd Order Intercept	40.0 dBm Typical
2 nd Order Intercept	49.0 dBm Typical
VSWR	1.2/2.0 Input Typ/Max 1.4/2.0 Output Typ/Max
Reverse Isolation	-11.0 dB Typical -10.5 dB Min
Power Supply	15.0 Volts 45.0 mA
Operating Temperature	-55.0 - 85.0 °C

Package Drawing


SM-19 Surface Mount Package




Gain




Noise Figure




P_{1dB} Compression Point




Reverse Isolation



Input VSWR



Output VSWR



S-Parameters

Frequency	S11 Mag	S11 Ang	S21 Mag	S21 Ang	S12 Mag	S12 Ang	S22 Mag	S22 Ang
10.0	0.100	128.00	2.720	6.00	0.270	8.00	0.170	151.00
50.0	0.050	145.00	2.730	-10.00	0.270	-10.00	0.130	151.00
100.0	0.040	155.00	2.730	-23.00	0.270	-24.00	0.130	133.00
150.0	0.040	167.00	2.720	-36.00	0.270	-36.00	0.120	117.00
200.0	0.050	-179.00	2.740	-48.00	0.270	-50.00	0.110	104.00
250.0	0.080	-171.00	2.750	-61.00	0.270	-62.00	0.100	102.00

Absolute Maximum Conditions

Maximum Operating Temperature	-55.0 - 100.0 °C	Maximum Storage Temperature	-62.0 - 125.0 °C
Maximum Case Temperature	125.0 °C	Maximum Supply Voltage	18.0 Volts
Continuous RF Input Power	18.0 dBm	Short Term RF Input Power (1 minute max)	50.0 mW
Maximum Peak Power (3 µsec max)	0.5 W		

Amplifonix | 2707 Black Lake Place | Philadelphia, PA 19154
Tel: 215.464.4000 | FAX: 215.464.4001 | Email: info@amplifonix.com

i2 Technologies US, Inc.

HTML Pages converted to PDF Document

This document contain component information from the manufacturer's website which are not available in a revision controlled document from the manufacturer. To facilitate the addition of these parts into the Electronics Database, we are converting the HTML pages related to that part, from the manufacturer's website into Adobe PDF format. The contents of this document is based on the information provided on the manufacturer's website, therefore the information may have been changed by the manufacturer since this was created.

