



GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:
SEE DRAWING C01-8646-0000

TIN-LEAD PART-NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	G±0.25	PART NUMBER
09	30.81	24.99	16.96	16.79	5.90	D09P25K*PA00
15	39.14	33.32	25.18	25.12	5.90	D15P25K*PA00
25	53.03	47.04	39.12	38.84	5.70	D25P25K*PA00
37	69.32	63.50	55.68	55.30	5.70	D37P25K*PA00

Plating: 4 ---> flash AU
Plating: 5 ---> 0.4» AU
Plating: 6 ---> 0.76» AU

LEAD-FREE PART-NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D±0.25	G±0.25	PART NUMBER
09	30.81	24.99	16.96	16.79	5.90	D09P25K*PA00LF
15	39.14	33.32	25.18	25.12	5.90	D15P25K*PA00LF
25	53.03	47.04	39.12	38.84	5.70	D25P25K*PA00LF
37	69.32	63.50	55.68	55.30	5.70	D37P25K*PA00LF

Plating: 4 ---> flash AU
Plating: 5 ---> 0.4» AU
Plating: 6 ---> 0.76» AU

European Views

www.fciconnect.com		surface	ISO 1302	tolerance std	ISO 406 ISO 1101	projection	mm
Dr JARRY		ANGULAR	✓	TOLERANCES UNLESS OTHERWISE SPECIFIED		±0.1	Scale 2
Eng PESSON	1994-04-20	LINEAR		0.X	±0.1	A3	ECN 109-0268
Chr NIRMAL GEORGE	2009-11-24	0.XX		0.XXX	±0.1		
Appr SUDHIR VARMA	2009-11-24	Product family		D-SUB	Spec ref		

FCI		MALE CONNECTOR		C01-8646-0242		Rev. F
e catalog no		WIRE WRAP (3 LEVELS)		CUSTOMER		sheet 1 of 1

rev	ecn no	dr	date
C	-	SJO	1997/09/05
D	LS06-0074	LGO	2006/05/10
E	LS06-0097	LGO	2006/07/29
F	109-0268	NG	2009-11-24