

Technology to Inspire Innovation

# ***Preferred Connector Products***

# **JAE**



***JAE Electronics, Inc.***

***For Additional Information Visit [www.jae-connector.com](http://www.jae-connector.com)***

**J**apan Aviation Electronics Industry, Ltd. (JAE) is an international manufacturer and supplier of electronic components and systems. For over four decades, JAE has provided the electronics industry with solutions to complex design requirements. Since its founding, the Company has strived to contribute to society through market-driven, technology-based global business operations under the philosophy: "Technology to Inspire Innovation."

With worldwide and world-class manufacturing certified to ISO 9001 and QS 9000, JAE has made the commitment to meet the global requirements of our customer. In addition to a network of state of the art manufacturing facilities, JAE has technical service offices located around the world, staffed with experts in connector design and application.

This catalog contains a select overview of JAE Connector Products. For in-depth information on our complete product line, and information on new developments, visit JAE's online catalog at [www.jae-connector.com](http://www.jae-connector.com).

Innovative design, quality oriented manufacturing, commitment to our customers and sensitivity to the environment assures JAE's leadership position in the 21<sup>st</sup> century.

## Table of Contents

Product Series	Contact Spacing	Pages
<b>SOCKETS/MEMORY PRODUCTS</b>		
PCMCIA		
JC22.....	1.27mm (.050").....	5
COMPACT FLASH		
JC26C2.....	1.27mm (.050").....	6 - 7
JC26E.....	1.27mm (.050").....	8
JC26F.....	1.27mm (.050").....	9
PCI EXPRESS MINI CARD		
MM60.....	0.8mm (.031").....	10
EXPRESSCARD		
PX10/11.....	1.0mm (.039").....	11 - 12
PX20/22.....	1.0mm (.039") / 0.635mm (.025").....	13 - 14
SMART/SIM CARD		
SF2.....	2.54mm (.100").....	15
SF3.....	2.54mm (.100").....	16
SF6.....	2.54mm (.100").....	17
SF7.....	2.54mm (.100").....	18
SF7 (Slim).....	2.54mm (.100").....	19
SF9.....	2.54mm (.100").....	20
SECURE DIGITAL CARD		
SG5.....	2.50mm (.098").....	21
MINI SECURE DIGITAL CARD (SD)		
ST4.....	1.1mm (.043").....	22
SC1.....	2.50mm (.098").....	23
MICRO SD/TRANSFLASH™		
ST1.....	1.1mm (.043").....	24
ST2.....	1.1mm (.043").....	25

## **BOARD-TO-BOARD CONNECTOR PRODUCTS**

BOARD-TO-BOARD		
AA03.....	0.40mm (.020").....	26
WA6.....	0.40mm (.020").....	27
WH1.....	0.40mm (.020").....	28
AA01A.....	0.50mm (.020").....	29
IL-312.....	0.50mm (.020").....	30
WR.....	0.50mm (.020").....	31 - 32
WB3.....	0.50mm (.020").....	33
IL-WX.....	0.80mm (.031").....	34
KX14/15.....	0.80mm (.031").....	35 - 36
PM1.....	0.80mm (.031").....	37
WM1.....	1.00mm (.039").....	38
WM2.....	1.00mm (.039").....	39
TX24/TX25.....	1.27mm (.050").....	40

## Table of Contents

Product Series	Contact Spacing	Pages
<b>BOARD-TO-BOARD CONNECTOR PRODUCTS</b>		
WIRE-TO-BOARD		
PCB-TO-FPC/FFC		
FB3.....	0.30mm (.012").....	41
FB5.....	0.30mm (.012").....	42
FB6.....	0.30mm (.012").....	43
FF02.....	0.30mm (.012").....	44
FF02S.....	0.30mm (.012").....	45
FB8.....	0.30mm (.012").....	46
FA5.....	0.50mm (.020").....	47
FF03.....	0.50mm (.020").....	48
IL-FPR.....	0.50mm (.020").....	49
PCB-TO-CABLE/FPC		
FI-J.....	0.40mm (.016").....	50 - 51
FI-R.....	0.50mm (.020").....	52 - 53
FI-X.....	1.00mm (.039").....	54 - 55
FI.....	1.25mm (.049").....	56 - 58
PCB-TO-CABLE		
DX2/3.....	0.80mm (.031").....	59
FI-E.....	1.00mm (.039").....	60 - 61
CN10.....		62 - 63
CV10.....		64
IL-Z.....	1.25mm (.049").....	65 - 66
IL-S.....	2.00mm (.079").....	67 - 68
LY.....	2.00mm (.079").....	69
KD10/20.....	2.00mm (.079").....	70
IL-G.....	2.50mm (.098").....	71
<b>INPUT/OUTPUT CONNECTOR PRODUCTS</b>		
PCB-TO-CABLE		
DD1.....	0.50mm (.020").....	72 - 73
DD2.....	0.50mm (.020").....	74 - 75
DG1.....	0.50mm (.020").....	76
RA1.....	0.50mm (.020").....	77
RC1.....	0.50mm (.020").....	78
DA1.....	0.60mm (.024").....	79
DE1.....	1.27mm (.050").....	80
TX20A.....	1.27mm (.050").....	81
DV2.....	1.905mm (.075").....	82 - 84
CIRCULAR		
JN1.....		85 - 86
JN2.....		87 - 88
JB5.....		89

## Table of Contents

*Product Series*                      *Contact Spacing*                      *Pages*

### INPUT/OUTPUT CONNECTOR PRODUCTS

#### CIRCULAR

JL04V .....	90 - 91
JL05 .....	92 - 93
JB1 .....	94 - 95
SRCN .....	96 - 97
N/MS .....	98 - 99

### FIBER OPTIC PRODUCTS

FO-FC .....	100
FO-EX .....	101

### AUTOMOTIVE CONNECTOR PRODUCTS

#### PCB-TO-CABLE

MX34 .....	1.1mm (.043")	102
MX7 .....	2.30mm (.091")	103
IL-AG7 .....	2.50mm (.098")	104
MX17 .....	2.50mm (.098")	105 - 106
MX23A .....	2.50mm (.098")	107 - 108
MX10 .....	2.50mm (.098")	109
MX5 .....	3.00mm (.118")	110

#### PCB-TO-CABLE/CABLE-TO-CABLE

IL-AG5 .....	2.50mm (.098")	111
IL-AG6 .....	2.50mm (.098")	112
MX9 .....	3.50mm (.138")	113
MX25 .....	6.7mm (2.64")	114
MX36 .....	2.50mm (.098")	115

#### CABLE-TO-CABLE

IL-AG9 .....	2.50mm (.098")	116 - 118
MX19 .....	2.50mm (.098")	119

- All JAE connector products shown in this catalog are lead free.
- We reserve the right to modify designs in order to improve quality, keep pace with technological advancements or meet particular requirements in production.
- Products shown in this catalog are made for the applications specified. However, if the above-mentioned products are to be used in aerospace devices, marine cable-connection devices, atomic power control systems, medical equipment for life-support systems, or any other specific application requiring extremely high reliability, please contact JAE for further information. Recommended Applications: Computers, Office Machines, Measuring Devices, Telecommunications Devices (Terminals, Mobile Devices) AV Devices, Household Applications, FA Devices, etc.
- Refer to end of catalog for alphabetical index of products.

# CN10 SERIES CONNECTORS

## Miniature Coaxial Connectors



### FEATURES


- Miniature connectors for board-to-coaxial jumper cable applications. Designed per MIL SMB type and JIS-C-5415
- Applicable frequency range is zero through 3 GHz. High impedance matching: the voltage standing wave ratio is less than 1.1 (Right-angle receptacle is 1.2 max. voltage standing wave ratio.)
- Low profile: the height on the board is 8mm (.315") to 9mm (.354") when a right-angle plug is mated with a straight receptacle
- An extrusion on the shell innerwall of the plug ensures mechanical and electrical integrity
- Plugs are supplied as cable assemblies
- The straight receptacle and board-in plug have kinked leads to hold connector during soldering



Miniature connectors for board-to-jumper coaxial cable applications intended for transmission of high frequency waves and high density packaging in electronic devices. With the combination of three types of receptacle (straight, right-angle and bulkhead) and three types of plug (straight, right-angle and board-in), it is feasible to have various connection styles. Suitable for use in automotive telephone sets, portable telephone sets, various communication devices and electronic measuring instruments.

### GENERAL SPECIFICATIONS

Characteristic Impedance	50 ohms
Current Rating	DC 2 Amps per contact
Voltage Rating	100 VAC r.m.s. (for one minute)
Dielectric Withstanding Voltage	200 VAC r.m.s. (for one minute)
Insulation Resistance	500 megohms min. (DC 250 V)
Contact Resistance	Center Contacts: 8 milliohms (max.) Outer Contacts: 8 milliohms (max.)
Voltage Standing Wave Ratio	1.2 max. (DC -3 GHz)
Total Mating Force	49N (max.)
Total Unmating Force	8.8 N (max.)
Operating Temperature Range	-55°C to +165°C (Connector only) Only right-angle receptacle is -40°C ~ 85°C
Applicable Cables	1.5 D-QEV (1.5 D-2V) 1.5 D-QEW (1.5 D-2W) 0.8 D-QEW (0.8 D-2W)



Dimensions and specifications subject to change without notice.

# CN10 SERIES CONNECTORS







## Miniature Coaxial Connectors

### STANDARD CABLE ASSEMBLIES (PLUG INCLUDED)

- For plug side, cable harnessed plug will be supplied
- The length (L in the figure below) is 100mm (3.937")
- For other lengths, consult JAE

### Part No. Explanation

	CN10	-	CA	100	-	RPL	-	*	-	E
	CN10	-	CA	100	-	BI	PL	-	*	E
Series										
Cable Harness Mark										
Cable Length										
L - 100mm										
Connector Configuration										
PL - Straight Plug										
RPL - Right-Angle Plug										
Connector Configuration										
PL - Straight Plug										
RPL - Right-Angle Plug										
Applicable Cable										
15 DV - 1.5D-QEV (1.5D-2V)										
15DW - 1.5D-QEW (1.5D-2W)										
8 DW - 0.8D-QEW (0.8D-2W)										
Lead Free Version										

		Applicable Cable	Part Number
Single-end termination	<b>• Right-angle plug</b> 	1.5D -QEV (1.5D-2V)	CN10-CA100-RPL-15DVE
		1.5D -QEW (1.5D-2W)	CN10-CA100-RPL-15DWE
	<b>• Straight plug</b> 	1.5D -QEV (1.5D-2V)	CN10-CA100-PL-15DV
		0.8D -QEW (0.8D-2W)	CN10-CA100-PL-15DW
Double-end termination	<b>• Right-angle plug</b> 	1.5D -QEW (1.5D-2W)	CN10-CA100-PL-8DW
		0.8D -QEW (0.8D-2W)	CN10-CA100-RPL-RPL-15DW
	<b>• Right-angle plug and Board-in type</b> 	1.5D -QEW (1.5D-2W)	CN10-CA100-BI-RPL-15DV
		0.8D -QEW (0.8D-2W)	CN10-CA100-BI-RPL-15DW
	<b>• Straight plug and Board-in type</b> 	1.5D -QEW (1.5D-2W)	CN10-CA100-BI-PL-15DV
		1.5D -QEW (1.5D-2W)	CN10-CA100-BI-PL-15DW
	<b>• Straight plug and Right-angle plug</b> 	0.8D -QEW (0.8D-2W)	CN10-CA100-BI-PL-8DW
		1.5D -QEW (1.5D-2W)	CN10-CA100-RPL-15DW

Dimensions in mm (inches).

Technology to Inspire Innovation

# JAE

***“Building Technologies  
to Connect Your World”***



## **Japan Aviation Electronics Industry, Limited**

1-19, Aobadai 3-chome, Meguro-ku  
Tokyo 153-8539, Japan  
Telephone: 03-3780-2736  
Fax: 03-3780-2883

## **JAE Electronics, Inc.**

142 Technology Drive, Suite 100  
Irvine, California 92618-2430, U.S.A.  
Telephone: 949-753-2600  
Fax: 949-753-2699  
800-523-7278 Toll free in the U.S.A.

## **JAE Europe**

Coliseum Business Centre  
Riverside Way, Camberley  
Surrey, GU15 3YL, England  
Telephone: 44-1276-404000  
Fax: 44-1276-404010

## **JAE Taiwan, Ltd.**

4F-1, No. 88, Chung Hsiao E. Rd.  
Sec. 2, Taipei, Taiwan, R.O.C.  
Telephone: 886-2-2396-7676  
Fax: 886-2-2392-5929

## **JAE Hong Kong, Ltd.**

Suites 1407-11, 14/F, Tower 2, The Gateway,  
25 Canton Road, Tsimshatsui, Kowloon, Hong Kong  
Telephone: 852-2723-7782  
Fax: 852-2723-9028

## **JAE Korea, Inc.**

1602, Korea City Air Tower  
159-9 Samsung-Dong, Kangnam-ku  
Seoul, 135-973, Korea  
Telephone: 82-2-551-8959  
Fax: 82-2-551-8958

## **JAE Philippines, Inc.**

PEZA Zone, Gateway Business Park, Javalera  
General Trias, 4107 Cavite, Philippines  
Telephone: 63-46-433-0285  
Fax: 63-46-433-0287

## **JAE Singapore Pte., Ltd.**

33 Tannery Lane, #02-01 Hoesteel  
Industrial Building  
Singapore 347789  
Telephone: 65-6748-1332  
Fax: 65-6748-2920

## **JAE Shanghai Co., Ltd.**

RM 1407, Shanghai Mart 2299 Yanan Rd.  
West Shanghai 200336 P.R.C.  
Telephone: 86-21-6236-0322  
Fax: 86-21-6236-1292