

SMB Tee Adapter Plug-Jack-Jack



TECHNICAL DATA SHEET

SMB Tee Adapter Plug-Jack-Jack	
Configuration Connector 1 Impedance 1 Connector 2 Impedance 2 Connector 3 Adapter Design Body Style	SMB Plug 50 Ohms SMB Jack 50 Ohms SMB Jack Standard Tee
Mechanical Specifications	
Size Length, in [mm] Width/Dia., in [mm] Height, in [mm]	0.788 [20.02] 0.25 [6.35] 0.525 [13.34]
Connector 1 Type Inner Conductor Material and Plating Body Material and Plating Dielectric Type	SMB Plug Gold Brass, Nickel PTFE
Connector 2 Type Inner Conductor Material and Plating Body Material and Plating Dielectric Type	SMB Jack Gold Brass, Nickel PTFE
Connector 3 Type Inner Conductor Material and Plating Body Material and Plating Dielectric Type	SMB Jack Gold Brass, Nickel PTFE
Compliance Certifications (visit www.Pasternack.com for current document) RoHS Compliant Yes	
Plotted and Other Data Notes:	Values at 25 °C, sea level
URL: http://www.pasternack.com/smb-plug-jack-jack-tee-adapter-pe9309-p.aspx	
SMB Tee Adapter Plug-Jack-Jack from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the	

industry. The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improve-

ments. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

Pasternack Enterprises, Inc. • P.O. Box 16759, Irvine, CA 92623 **Phone:** (866) 727-8376 or (949) 261-1920 • **Fax:** (949) 261-7451 Sales@Pasternack.com • Techsupport@Pasternack.com



PE9309

PE9309 CAD Drawing

SMB Tee Adapter Plug-Jack-Jack

