


Type AB Right Angle Female for Daughter Cards

Series 8071



- 110 contacts in a 5 x 22 configuration
- Available with or without upper shield
- Designed for gas tight press-fit installation
- Available with or without upper ground return shield
- Prealignment guides
- This connector can be used by itself or in conjunction with a Type A, B, C female connector




27 8071 110 003 XXX+ = Type B 22 Vertical Female without upper shield

27 8071 110 013 XXX+ = Type B 22 Vertical Female with upper shield

XXX =


Plating Code	Contact Area	Press-fit Area	Under Coat
833	0.1µm min. Au.65µm Pd/Ni	1.5-3.0µm Sn	Nickel 1.2-3.0µm Ni
863	0.76µm min. Au	1.5-3.0µm Sn	Nickel 1.2-3.0µm Ni





Type AB Right Angle Female for Daughter Cards

Series 8071






- 125 contacts in a 5 x 25 configuration
- Available with or without upper shield
- Designed for gas tight press-fit installation
- Available with or without upper ground return shield
- Prealignment guides
- This connector can be used by itself or in conjunction with Type A, B & C female connectors



27 8071 125 003 863+ = Type AB Right Angle Female without upper shield
27 8071 125 013 863+ = Type AB Right Angle Female with upper shield

Plating Code	Contact Area	Press-fit Area	Under Coat
863	0.76µm min. Au	1.5-3.0µm Sn	1.2-3.0µm Ni



RECOMMENDED P.C. BOARD LAYOUT (COMPONENT SIDE)

