

August 1991

Features


- 7A and 8A, 450V - 500V
- $r_{DS(on)} = 0.85\Omega$ and 1.1Ω
- Single Pulse Avalanche Energy Rated*
- SOA is Power-Dissipation Limited
- Nanosecond Switching Speeds
- Linear Transfer Characteristics
- High Input Impedance

Description

The IRF440, IRF441, IRF442, and IRF443 are n-channel enhancement-mode silicon-gate power field-effect transistors. IRF440R, IRF441R, IRF442R and IRF443R types are advanced power MOSFETs designed, tested, and guaranteed to withstand a specified level of energy in the breakdown avalanche mode of operation. All of these power MOSFETs are designed for applications such as switching regulators, switching converters, motor drivers, relay drivers, and drivers for high-power bipolar switching transistors requiring high speed and low gate-drive power. These types can be operated directly from integrated circuits.


The IRF types are supplied in the JEDEC TO-204AA steel package.

Package



Terminal Diagram

N-CHANNEL ENHANCEMENT MODE



Absolute Maximum Ratings ($T_C = +25^\circ\text{C}$), Unless Otherwise Specified

	IRF440 IRF440R	IRF441 IRF441R	IRF442 IRF442R	IRF443 IRF443R	UNITS
Drain-Source Voltage (1)	V_{DS} 500	450	500	450	V
Drain-Gate Voltage ($R_{GS} = 20k\Omega$) (1)	V_{DGR} 500	450	500	450	V
Continuous Drain Current					
$T_C = +25^\circ\text{C}$	I_D 8.0	8.0	7.0	7.0	A
$T_C = +100^\circ\text{C}$	I_D 5.0	5.0	4.4	4.4	A
Pulsed Drain Current (3)	I_{DM} 32	32	28	28	A
Gate-Source Voltage	V_{GS} ± 20	± 20	± 20	± 20	V
Maximum Power Dissipation					
$T_C = +25^\circ\text{C}$	P_D 125	125	125	125	W
Linear Derating Factor	1.0	1.0	1.0	1.0	W/ $^\circ\text{C}$
Inductive Current, Clamped	I_{LM} 32	32	28	28	A
(See Figure 14, $L = 100\mu\text{H}$)					
Single Pulse Avalanche Energy Rating (4)	E_{AS}^* 510	510	510	510	mJ
Operating and Storage Junction	T_J, T_{STG} -55 to +150	-55 to +150	-55 to +150	-55 to +150	$^\circ\text{C}$
Temperature Range					
Maximum Lead Temperature for Soldering	T_L 300	300	300	300	$^\circ\text{C}$
(0.063" (1.6mm) from case for 10s)					

NOTES:


1. $T_J = +25^\circ\text{C}$ to $+150^\circ\text{C}$.
2. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.
3. Repetitive rating: Pulse width limited by maximum junction temperature. See Transient Thermal Impedance Curve (Figure 5).

*R Suffix Types Only

4. $V_{DD} = 50\text{V}$, starting $T_J = +25^\circ\text{C}$, $L = 14\text{mH}$, $R_{GS} = 25\Omega$, $I_{PEAK} = 8\text{A}$. See Figure 15.

IRF440, IRF441, IRF442, IRF443 IRF440R, IRF441R, IRF442R, IRF443R

Electrical Characteristics $T_C = 25^\circ\text{C}$, Unless Otherwise Specified

CHARACTERISTIC	SYMBOL	TEST CONDITIONS	LIMITS			UNITS	
			MIN	TYP	MAX		
Drain-Source Breakdown Voltage IRF440/442, IRF440R/442R IRF441/443, IRF441R/443R	BV _{DSS}	V _{GS} = 0V, I _D = 250 μ A	500	-	-	V	
			450	-	-	V	
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} = V _{GS} , I _D = 250 μ A	2.0	-	4.0	V	
Gate-Source Leakage Forward	I _{GSS}	V _{GS} = 20V	-	-	100	nA	
Gate-Source Leakage Reverse	I _{GSS}	V _{GS} = -20V	-	-	-100	nA	
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = Max Rating, V _{GS} = 0V	-	-	250	μ A	
		V _{DS} = Max Rating x 0.8, V _{GS} = 0V, T _J = +125 $^\circ$ C	-	-	1000	μ A	
On-State Drain Current (Note 2) IRF440/441, IRF440R/441R IRF442/443, IRF442R/443R	I _{D(ON)}	V _{DS} > I _{D(ON)} x r _{DS(ON)} Max, V _{GS} = 10V	8.0	-	-	A	
			7.0	-	-	A	
Static Drain-Source On-State Resistance (Note 2) IRF440/441, IRF440R/441R IRF442/443, IRF442R/443R	r _{DS(ON)}	V _{GS} = 10V, I _D = 4.4A	-	0.70	0.85	Ω	
			-	0.85	1.1	Ω	
Forward Transconductance (Note 2)	g _{ts}	V _{DS} \geq 50V, I _D = 4.4A	4.9	7.5	-	S(V)	
Input Capacitance	C _{iSS}	V _{GS} = 0V, V _{DS} = 25V, f = 1.0MHz See Figure 10	-	1225	-	pF	
Output Capacitance	C _{oSS}		-	200	-	pF	
Reverse Transfer Capacitance	C _{rSS}		-	85	-	pF	
Turn-On Delay Time	t _{d(ON)}	V _{DD} = 250V, I _D \approx 8A, R _G = 9.1 Ω See Figure 16. (MOSFET switching times are essentially independent of operating temperature)	-	15	21	ns	
Rise Time	t _r		-	22	35	ns	
Turn-Off Delay Time	t _{d(OFF)}		-	49	74	ns	
Fall Time	t _f		-	20	30	ns	
Total Gate Charge (Gate-Source + Gate-Drain)	Q _g	V _{GS} = 10V, I _D = 8A, V _{DS} = 0.8V Max Rating. See Figure 17 for test circuit. (Gate charge is essentially independent of operating temperature.)	-	42	63	nC	
Gate-Source Charge	Q _{gs}		-	9	-	nC	
Gate-Drain ("Miller") Charge	Q _{gd}		-	22	-	nC	
Internal Drain Inductance	L _D	Measured between the contact screw on header that is closer to source and gate pins and center of center of die.	Modified MOSFET symbol showing the internal device inductances.		-	5.0	nH
Internal Source Inductance	L _S	Measured from the source lead, 6mm (0.25") from header and source bonding pad.			-	12.5	nH
Junction-to-Case	R θ JC		-	-	1.0	$^\circ\text{C/W}$	
Case-to-Sink	R θ CS	Mounting surface flat, smooth and greased	-	0.1	-	$^\circ\text{C/W}$	
Junction-to-Ambient	R θ JA	Free air operation	-	-	30	$^\circ\text{C/W}$	

Source Drain Diode Ratings and Characteristics

Continuous Source Current (Body Diode)	I _S	Modified MOSFET symbol showing the integral reverse P-N junction rectifier.	-	-	8.0	A
Pulse Source Current (Body Diode) (Note 3)	I _{SM}		-	-	32	A
Diode Forward Voltage (Note 2)	V _{SD}	T _J = +25 $^\circ$ C, I _S = 8.0A, V _{GS} = 0V	-	-	2.0	V
Reverse Recovery Time	t _{rr}	T _J = +25 $^\circ$ C, I _F = 8.0A, dI _F /dt = 100A/ μ s	210	460	970	ns
Reverse Recovered Charge	Q _{RR}	T _J = +25 $^\circ$ C, I _F = 8.0A, dI _F /dt = 100A/ μ s	2	4	8.9	μ C
Forward Turn-on Time	t _{ON}	Intrinsic turn-on time is negligible. Turn-on speed is substantially controlled by L _S + L _D .	-	-	-	-

NOTES: 1. T_J = +25 $^\circ$ C to +150 $^\circ$ C

2. Pulse Test: Pulse width \leq 300 μ s, Duty Cycle \leq 2%

3. Repetitive Rating: Pulse width limited by max. junction temperature. See Transient Thermal Impedance Curve (Figure 5)

4. V_{DD} = 50V, Start T_J = +25 $^\circ$ C, L = 14mH, R_{GS} = 25 Ω , I_pPEAK = 8A (See Figure 15)

Performance Curves




FIGURE 1. TYPICAL OUTPUT CHARACTERISTICS




FIGURE 2. TYPICAL TRANSFER CHARACTERISTICS




FIGURE 3. TYPICAL SATURATION CHARACTERISTICS




FIGURE 4. MAXIMUM SAFE OPERATING AREA




FIGURE 5. MAXIMUM EFFECTIVE TRANSIENT THERMAL IMPEDANCE, JUNCTION-TO-CASE vs PULSE DURATION

4
N-CHANNEL
POWER MOSFETS

Performance Curves (Continued)




FIGURE 6. TYPICAL TRANSCONDUCTANCE vs DRAIN CURRENT




FIGURE 7. TYPICAL SOURCE-DRAIN DIODE FORWARD VOLTAGE




FIGURE 8. BREAKDOWN VOLTAGE vs TEMPERATURE




FIGURE 9. NORMALIZED ON-RESISTANCE vs TEMPERATURE




FIGURE 10. TYPICAL CAPACITANCE vs DRAIN-TO-SOURCE VOLTAGE




FIGURE 11. TYPICAL GATE CHARGE vs GATE-TO-SOURCE VOLTAGE

Performance Curves (Continued)




FIGURE 12. TYPICAL ON RESISTANCE vs DRAIN CURRENT




FIGURE 13. MAXIMUM DRAIN CURRENT vs CASE TEMPERATURE




FIGURE 14a. CLAMPED INDUCTIVE TEST CIRCUIT




FIGURE 15a. UNCLAMPED ENERGY TEST CIRCUIT




FIGURE 14b. CLAMPED INDUCTIVE WAVEFORMS




FIGURE 15b. UNCLAMPED ENERGY WAVEFORMS




FIGURE 16. SWITCHING TIME TEST CIRCUIT




FIGURE 17. GATE CHARGE TEST CIRCUIT