

SmartOnline 8kVA On-Line Double-Conversion UPS, 4U Rack/Tower, 208/120V or 240/120V NEMA & Hardwire outputs, Split phase input

MODEL NUMBER: **SU8000RT4U**



Description

Tripp Lite 8kVA SmartOnline Hot-Swappable Modular Rack/Tower UPS offers 8000VA on-line, double-conversion UPS support for server, network and telecommunications equipment. Maintains battery-derived AC output during blackouts with active, full-time power conditioning. Fault-tolerant auto-bypass prevents unexpected service interruptions during overload or internal fault conditions. Single all-in-one housing installs in 4 rack spaces (4U). Upright tower and two post rackmount installation supported with optional accessories. Maintains full-time sine wave output within 3% of selectable 208/120 or 240/120V AC. Corrects brownouts and overvoltages from 65V to 140V (L-N). Expandable runtime with optional external battery packs. Converts raw input from AC to DC, then resynthesizes output power back to perfect sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types. Highly efficient operation in optional economy mode setting, saving BTU heat output and energy costs. Network-grade AC surge and noise suppression. Network management interfaces include combination DB9 RS-232 enabled and dry contact serial port, enhanced USB port and SNMPWEBCARD slot. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X. Supports simultaneous detailed monitoring of equipment load levels, self-test data and utility power conditions via all 3 network interfaces. Includes PowerAlert monitoring software and complete cabling. Supports Emergency Power Off (EPO) via built-in interface. Front panel LEDs and LCD readout with scroll controls support visual monitoring of all major UPS functions. LED/LCD display panel easily rotates for viewing in rackmount or tower configurations. Split phase 4 conductor hardwire input. UPS supported outlets include two L6-30R, two L6-20R and 4 low voltage 5-15/20R. Hardwire output is also supported. Hardwire connections and outlets are mounted on a detachable backplate with manual bypass switch to enable hot-swappable UPS replacement without powering off connected equipment. Internal batteries and optional external battery packs are field replaceable and hot swappable. Attractive all-black color scheme. \$250,000 Ultimate Lifetime Insurance.

Features

- True online, double-conversion UPS provides pure, full-time sine wave AC output free of surges, voltage fluctuations and line noise
- 8000VA/5600 watt output power capacity with dual voltage output of 208/120 or 240/120V
- 4U all-in-one high power density housing supports rackmount installation in only 4 rack spaces

Highlights

- 8000VA / 8kVA / 5600W on-line double-conversion UPS
- 208/120V or 240/120V +/-3% output at 60Hz
- 4U Rack/Tower compatible, Hot-swap power and battery modules
- USB, RS232 & EPO ports, support for SNMP/WEB card options
- Front panel LEDs with detailed LCD monitoring and control screen
- Expandable runtime with optional external battery packs
- Hardwire input (4 wire), L6-30R, L6-20R, 5-15/20R & Hardwire outputs

Package Includes

- SU8000RT4U Smart Online UPS
- SUPDM8K Detachable PDU with Manual Bypass Switch
- PowerAlert software and complete cabling
- 4 post rackmount installation brackets



- Dual conversion UPS actively converts raw input from AC to DC, then back to perfect sine wave AC output with enhanced protection from harmonic distortion, fast electrical impulses and other hard-to-solve power problems not addressed by other UPS types
- Hardwire input/output connections and output receptacles are mounted on a detachable backplate with manual bypass switch to enable hot-swappable UPS replacement without powering off connected equipment
- Provides perfectly regulated, sine wave output power free of line noise, transient surges and frequency variation for the most efficient operation of critical servers, networking and telecommunications equipment
- Maintains output within 3% of selected 208/120 or 240/120V nominal voltage during brownouts and overvoltages
- Supports connected equipment during blackouts for 12/5 minutes at half/full load levels, runtime is further expandable with optional external battery packs
- Some external battery configurations require the use of Tripp Lite's External Battery Configuration Software (see manual)
- Network interfaces support simultaneous communications via DB9 port, USB port and SNMPWEBCARD slot. DB9 port supports RS-232 and dry contact messaging. HID-compliant USB interface enables integration with built-in power management and auto shutdown features of Windows and Mac OS X.
- Included PowerAlert UPS monitoring software supports safe unattended shutdown, monitoring and control via local connected servers, plus any number of additional servers over IP
- Communications ports support on-battery, low-battery, power-restored, AC-voltage, DC-voltage, output current monitoring, battery charge current, battery capacity, AC line frequency, timed inverter shutoff, activate self-test and output power control
- Built-in Emergency Power Off (EPO) interface with cable
- Includes hardwire output and 8 output receptacles (2 L6-30R, 2 L6-20R, 4 NEMA 5-15/20R), all of which are available for simultaneous use
- Split phase, 4 conductor hardwire connection (featured on included detachable PDU).
- Front panel LEDs and LCD readout with scroll button enables visual confirmation of all major UPS functions and current site electrical conditions
- Front panel switches enable power on/off control, self-test and alarm cancel functions
- Included adjustable mounting rails support installation in 4 post 19 inch rack enclosures
- Optional 2-9USTAND set of tower stands supports upright tower installation
- Optional 2POSTRMKITWM accessory enables 2 post rackmount installation
- Fault tolerant electronic bypass maintains utility output during a variety of UPS fault conditions
- \$250,000 Ultimate Lifetime Insurance (USA, Puerto Rico and Canada only)

Specifications

| OUTPUT | |
|---------------------------------------|--|
| Output Volt Amp Capacity (VA) | 8000 |
| Output kVA capacity (kVA) | 8 |
| Output Watt Capacity (watts) | 5600 |
| Output kW capacity | 5.6 |
| Output power factor | 0.7 |
| Output Capacity Details | 8,000 VA (240V) / 7200 VA (208V) / 5600 watts (208/240V) |
| Crest Factor | 3:1 |
| Nominal Output Voltage(s) Supported | 120V; 208V; 240V |
| Nominal Voltage details | 240/120V or 208/120V split phase output |
| Frequency compatibility | 60 Hz |
| Output voltage regulation (line mode) | +/- 3% |



| | |
|--|--|
| Output voltage regulation (Economy line mode) | +/- 10% |
| Output voltage regulation (Battery mode) | +/- 3% |
| Built-in UPS output receptacles | 4 5-15/20R outlet(s); 2 L6-20R outlet(s); 2 L6-30R outlet(s); Hardwire |
| Output circuit breaker | 20A branch rated breakers (x4) protect 1 5-15/20R outlet each, 20A double pole breakers (x2) protect one L6-20R each, L6-30R outlets are unbreakered |
| Output AC waveform (AC mode) | Sine wave |
| Output AC waveform (battery mode) | Pure Sine wave |
| INPUT | |
| Rated input current (at maximum load) | 34A |
| Nominal Input Voltage(s) Supported | 208V AC / 120V AC (4 wire split single phase); 240V AC /120V AC (4 wire split single phase) |
| UPS input connection type | Hardwire |
| UPS input connection description | 4 wire split-phase input (L1, L2, N, G) |
| Recommended Electrical Service | 40A 208/240-120V Split Phase |
| Phase | Single-Phase |
| BATTERY | |
| Full load runtime (minutes) | 5 min. (5600w) |
| Half load runtime (minutes) | 12 min. (2800w) |
| Expandable battery runtime | Supports extended runtime with optional external battery packs |
| External battery pack compatibility | BP192V12-3U ; BP192V557C-1PH ; BP192V787C-1PH ; BP192V1037C-1PH ; BP192V1407C-1PH |
| DC system voltage (VDC) | 192 |
| Battery recharge rate (included batteries) | Less than 6 hours from 10% to 80% |
| Replacement battery cartridge (internal UPS battery replacement) | RBC9-192 |
| Battery Access | Front panel battery access door |
| Battery replacement description | Hot-swappable, user replaceable batteries |
| VOLTAGE REGULATION | |
| Voltage regulation description | Online, double-conversion power conditioning |
| Overvoltage correction | 3% output voltage regulation during overvoltages to 140 (measured L1-N : L2-N) |
| Undervoltage correction | 2% output voltage regulation during undervoltages to 65 (measured L1-N : L2-N) |
| LEDS ALARMS & SWITCHES | |
| LED Indicators | 6 LEDs indicate line power, online mode, economy/bypass mode, on-battery, charger and AC output status; LCD screen offers additional information and control options |



| | |
|--|---|
| Alarms | Unique audible alarms for all major UPS, environmental and power conditions (see manual) |
| Alarm cancel operation | Alarm cancel switch |
| Switches | Includes main power off/on switch, plus 2 switches to set and execute scrollable LCD functions. A manual bypass switch featured on the detachable PDU allows for complete removal of the UPS during routine maintenance without disrupting output power |
| SURGE / NOISE SUPPRESSION | |
| UPS AC suppression response time | Instantaneous |
| EMI / RFI AC noise suppression | Yes |
| AC suppression response time | Instantaneous |
| PHYSICAL | |
| Installation form factors supported with optional accessories | 2 post rackmount (2POSTRMKITWM); Tower (2-9USTAND) |
| Primary form factor | Rackmount |
| UPS / Power Module dimensions in primary form factor (height x width x depth / inches) | 7 x 17.5 x 32.6 |
| UPS / Power Module dimensions in primary form factor (height x width x depth / cm) | 17.8 x 44.4 x 82.7 |
| Installed whole system maximum rack depth (inches) | 32.6 |
| Installed whole system maximum rack depth (cm) | 82.7 |
| Rack Height | 4U |
| Secondary form factor | Tower (requires 2-9USTAND) |
| UPS / Power Module weight (lbs) | 177 |
| UPS / Power Module weight (kg) | 80.4 |
| UPS dimensions details | 4U UPS with internal batteries |
| UPS Shipping dimensions (height x width x depth / inches) | 13 x 23 x 37 |
| UPS Shipping dimensions (height x width x depth / cm) | 33 x 58.4 x 94 |
| Shipping weight (lbs) | 212 |
| Shipping weight (kg) | 96.2 |
| Cooling method | Fans |
| UPS housing material | Steel |
| ENVIRONMENTAL | |
| Operating Temperature Range | +32 to +104 degrees Fahrenheit / 0 to +40 degrees Celsius |



| | |
|---|---|
| Storage Temperature Range | +5 to +122 degrees Fahrenheit / -15 to +50 degrees Celsius |
| Relative Humidity | 0 to 95%, non-condensing |
| AC mode BTU / hr. (full load) | 2353.3 |
| Battery mode BTU / hr. (full load) | 1883.1 |
| AC mode efficiency rating (100% load) | 89% |
| Operating Elevation (ft.) | 0-3000m (0 to 10,000 ft.) |
| Audible Noise | 60 dBA at front side 1 meter |
| Operating Elevation (m) | 0-3000 m |
| COMMUNICATIONS | |
| Communications interface | USB (HID enabled); DB9 Serial; Contact closure; EPO (emergency power off); Slot for SNMP/Web interface |
| Network monitoring port description | RS232 and contact closure communications are supported on one DB9 port |
| PowerAlert software | Included |
| Communications cable | USB and DB9 cabling included |
| LINE / BATTERY TRANSFER | |
| Transfer time | No transfer time (0 ms.) in online, double-conversion mode |
| Low voltage transfer to battery power (setpoint) | 65V (L1-N:L2-N) |
| High voltage transfer to battery power (setpoint) | 140V (L1-N:L2-N) |
| SPECIAL FEATURES | |
| Cold Start (startup in battery mode during a power failure) | Cold-start operation supported |
| High availability UPS features | Automatic inverter bypass; Manual bypass switch; Detachable hot-swap PDU; Hot swappable UPS power module; Hot swappable batteries |
| Green & high efficiency features | High efficiency economy mode operation; Schedulable daily hours of economy mode operation |
| CERTIFICATIONS | |
| UPS Certifications | Tested to UL1778 (USA); Tested to CSA (Canada); Tested to NOM (Mexico); Meets FCC Part 15 Category A (EMI) |
| WARRANTY | |
| Product Warranty Period (Worldwide) | 2-year limited warranty |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$250,000 Ultimate Lifetime Insurance |

Related Items



Optional Products

| Model Number | Description | Qty. |
|---------------------------------|---|------|
| 2-9USTAND | Enables Tower Placement of Rackmount UPS Systems | 1 |
| AS400CABLE KIT | Power Management Tools - UPS Communication Cable Kit for System i / AS400 / iSeries Servers | 1 |
| SNMPWEBCARD | For remote monitoring and control via SNMP, Web, or Telnet. | 1 |
| ENVIROSENSE | Monitors temperature, humidity and contact-closure inputs. (Requires SNMPWEBCARD or switched PDU.) | 1 |
| WEXT3-SU8000 | 3-Year Extended Warranty - For SU8000 models | 1 |
| WEXT5-SU8000 | 5-Year Extended Warranty - For SU8000 models | 1 |
| DCATV | Network Surge Suppressor - Essential protection for TV/VCR coaxial lines | 1 |
| DNET1 | Network Surge Suppressor - Essential protection for data and communication lines | 1 |
| DTEL2 | Network Surge Suppressor - Essential protection for data and communication lines | 1 |
| BP192V557C-1PH | External battery pack for use with select Tripp Lite UPS Systems | 1 |
| BP192V787C-1PH | External battery pack for use with select Tripp Lite UPS Systems | 1 |
| BP192V1037C-1PH | External battery pack for use with select Tripp Lite UPS Systems | 1 |
| BP192V1407C-1PH | External battery pack for use with select Tripp Lite UPS Systems | 1 |
| SUPDMB568HW | SUPDMB568HW - UPS Accessory - Hardwire PDU Module | 1 |
| BP192V12-3U | BP192V12-3U - External Battery Pack for UPS System | 1 |
| MODBUSCARD | For remote monitoring and control via MODBUS protocol | 1 |
| 2POSTRMKITHD | Enables 2-Post Rackmount Installation of 3U and Larger UPS, Transformer and Battery Pack Components | 1 |

More information, including related products, owner's manuals, and additional technical specifications, can be found online at:

<http://www.tripplite.com/sku/SU8000RT4U>.

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Tripp Lite:](#)

[SU8000RT4U](#)