


Specification	AXX3225L	Issue: 01	Date: 2006-03-18
Oscillator type : Quartz Crystal Unit in SMD package 3.2x2.5 mm			
Low frequency version operating in "Lame" contour mode			
RoHS compliant			

Parameter	min.	typ.	max.	Unit	Condition
Frequency range	3		5	MHz	
Actual frequency f_0				MHz	
Crystal cut / Vibration mode	GT / Lame mode				
Load capacitance C_L	10 ~ 50 pF or Series				
Adjustment tolerance	-30		+30	ppm	@ 25°C ±5°C
Frequency stability				ppm	Overall (Note 1)
Frequency stability over temperature range	+10 ~ -50			ppm	See chart for typical f(T) characteristic
operating temperature range (steady state)	-10		+60	°C	
long term (aging)			±5	ppm	
Resonance resistance R_r			500	Ω	@ 3 MHz
			150	Ω	@ 5 MHz
Motional capacitance C_1				fF	
Static capacitance C_0				pF	
Drive level		20	200	μW	
Insulation resistance	500			MΩ	100 V DC
Storage temperature range	-40		+85	°C	
Enclosure (see drawing)	3.2 x 2.5 x 0.7				IEC 61637
marking	Frequency (MHz) + Date Code				
Packing	Tape & Reel				IEC 60286-3


Notes:

1. Overall frequency stability = initial tolerance + temp. stability + aging (1st year)
2. Terminology and test conditions are according to IEC standard IEC60122-1, unless otherwise stated
3. Measurement technique according to IEC 60444-5 or equivalent

Typical Frequency vs. Temperature Characteristic



Enclosure drawing



Environmental conditions

Test	IEC 60068 Part ...	IEC 61178-1 clause ...	Test conditions
Visual inspection, dimensions		4.5 4.6	Enclosure styles as in IEC 60122-3, if applicable
Sealing tests	2-17	4.8.2	Gross leak: Test Qc, Fine leak: Test Qk
Solderability Resistance to soldering heat	2-20	4.8.3	Test Ta (235 ± 5)°C Method 1 Test Tb Method 1A, 5s
Shock	2-27	4.8.8	Test Ea, 3 x per axes 100g, 6 ms half-sine pulse
Bump	2-29	4.8.6	Test Eb, 4000 bumps per Axes, 40g, 6 ms
Free fall	2-32	4.8.9	Test Ed procedure 1, 2 drops from 1m height
Vibration, sinusoidal	2-6	4.8.7	Test Fc, 30 min per axes, 10 Hz - 55 Hz 0,75mm; 55 Hz - 1 kHz, 10g
Rapid change of temperature	2-14	4.8.5	Test Na, 10 cycles at extremes of operating temperature range
Dry heat	2-2	4.8.11	Test Ba, 16 h at upper temperature indicated by climatic category
Damp heat, cyclic	2-30	4.8.12	Test Db variant 1 severity b), 55°C/95% r.H., 6 cycles
Cold	2-1	4.8.13	Test Aa, 2 h at lower temperature indicated by climatic category
Climatic sequence	1-7	4.8.14	Sequence of 4.8.11, 4.8.12 (1 st cycle), 4.8.13, 4.8.12 (5 cycles)
Damp heat, steady state	2-3	4.8.15	Test Ca, 56 days
Endurance tests - ageing - extended aging		4.9.1 4.9.2	30 days @ 85°C 1000h, 2000h, 8000h @ 85°C