



All dimensions are in mm; tolerances according to ISO 2768 m-H

Documents

N/A

Material and plating

Connector parts

Connector body

Material

CuBe

Plating

AuroDur®, gold plated

ADAPTOR, MINI POWER
Mini-Coax PLUG - PLUG

23S122-S10L

Electrical data

Contact resistance ≤ 3 mΩ
Contact current 10 A

Mechanical data

Mating cycles ≥ 500
Engaging and disengaging force 1 N to 4 N

Environmental data

Temperature range -40°C to +85°C
Climatic class IEC 60068-2-1 40/85/21
IEC 60068-2-2
IEC 60068-2-3
Mechanical shock IEC 60068-2-27 50G halfsinus, 2 shocks/axis during 11 sec.
2002/95/EC (RoHS) compliant

Tooling

N/A

Suitable cables

N/A

Packing

Standard 100 pcs in blister
Weight 0.5 g/pce

While the information has been carefully compiled to the best of our knowledge, nothing is intended as representation or warranty on our part and no statement herein shall be construed as recommendation to infringe existing patents. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Draft	Date	Approved	Date	Rev.	Engineering change number	Name	Date
Rong Fang	21/04/05	Rong Fang	08/08/07	a00	07-0154	S. Huber-Siegl	08/08/07
Rosenberger Hochfrequenztechnik GmbH & Co. KG P.O.Box 1260 D-84526 Tittmoning Germany www.rosenberger.de				Tel.: +49 8684 18-0 Fax: +49 8684 18-499 email: info@rosenberger.de			Page 2 / 2