

Elevated-Feed-Point

High Tech, 3 dB Gain Antennas

Models

**ASP-910 • ASP-911 • ASP-912 • ASP-915
ASPG918 • ASPG919**

Attractive — all-black DURA-COAT™ appearance complements new vehicle styling

High Performance — elevated-feed-point design provides omnidirectional coverage when off-roof mounting is necessary

Versatile — ground-plane-independent design allows installation wherever necessary . . . convertibles, special mounts, even temporary fixed applications

Problem Solver — corrects coverage problems caused by misapplication of rooftop antennas

Antenna Mounting Options

ASP-910 Series
Complete 3/4 inch hole mount antenna including 17 ft (5.2 m) cable and connector.

ASP-911 Series
Adjustable angle (up to 15°), 7/8 - 15/16 inch hole mount antenna with integral N female connector. Cable (K-301 through K-304) available separately.

ASP-912 Series
"Quick Grip"™ trunk lid mount antenna including 17 ft (5.2 m) cable and connector.

ASPG918 & ASPG919
7/8 - 15/16 inch hole mount antennas with integral N female connector. No spring or angle adjustment. Cable (K-301 through K-304) available separately.

Specifications	
Electrical	
Power	40 watts 10 watts (ASPG918, ASPG919)
Gain	3 dBd (5 dBi) 4.2 dBd (ASPG919)
Frequency Range	806-869 MHz (ASPA & ASPSA prefix) 890-960 MHz (ASPG prefix) 902-960 MHz (ASPG918)
VSWR	1.9:1
Impedance	50 ohms
Mechanical	
Whip Material	One-piece stainless steel collinear with black DURA-COAT finish. Mounting this series of antennas in a location where it may be struck below the stainless steel whip is not recommended
Antenna Length	Approx. 24 inches (61 cm)
Spring Material	Stainless steel, black DURA-COAT
Base and Fittings	Positive male-female contact with stainless steel, plated steel, aluminum or brass parts
Cable	17 ft (5.2 m) PRO-FLEX™ PLUS (where supplied - see table below)
Connector	See table (crimp tool required for most connectors)

Available Model Configurations

Mount & Cable	Connector			No Connector or Cable
	Mini-UHF Male	N Male	TNC Male	
3/4 inch Hole Mount		ASPA910N	ASPA910T ASPG910T	
Angle Adjustable				ASPSA911 ASPG911
"Quick Grip" No Hole Trunk Lid Mount	ASPSA912M		ASPSA912T ASPRG912T	
Conversion Antenna				ASPA915 ASPG915
Fixed Station				ASPG919 ASPG918

ASP-915 Series
Replacement conversion antenna for ASP-910 and ASP-912 Series. No mount or cable. Fits A/S low profile "male-female contact" mount. See table for frequency ranges.