

ICE35N60W


N-Channel Enhancement Mode MOSFET

Features:


- Low $r_{DS(on)}$
- Ultra Low Gate Charge
- High dv/dt Capability
- High Unclamped Inductive Switching (UIS) Capability
- High Peak Current Capability
- Increased Transconductance Performance
- Optimized Design For High Performance Power Systems

Product Summary			
I_D	$T_A = 25^\circ\text{C}$	35A	Max
$V_{(BR)DSS}$	$I_D = 250\mu\text{A}$	600V	Min
$r_{DS(ON)}$	$V_{GS} = 10\text{V}$	0.075Ω	Typ
Q_g	$V_{DS} = 480\text{V}$	187nC	Typ

Pin Description:



TO-247



Maximum Ratings @ $T_j = 25^\circ\text{C}$, Unless Otherwise Specified

Symbol	Parameter	Value	Unit	Conditions
I_D	Continuous Drain Current	35	A	$T_C = 25^\circ\text{C}$
$I_{D, \text{pulse}}$	Pulsed Drain Current	103	A	$T_C = 25^\circ\text{C}$
E_{AS}	Avalanche Energy, Single Pulse	1100	mJ	$I_D = 18\text{A}$
I_{AR}	Avalanche Current, Repetitive	18	A	Limited by $T_{j, \text{max}}$
dv/dt	MOSFET dv/dt Ruggedness	50	V/ns	$V_{DS} = 480\text{V}$, $I_D = 35\text{A}$, $T_j = 125^\circ\text{C}$
V_{GS}	Gate Source Voltage	± 20	V	Static
		± 30		AC ($f > \text{Hz}$)
P_{tot}	Power Dissipation	313	W	$T_C = 25^\circ\text{C}$
T_j, T_{stg}	Operating and Storage Temperature	-55 to +150	$^\circ\text{C}$	
	Mounting Torque	60	Ncm	M 2.5 screws

Symbol	Parameter	Values			Unit	Conditions
		Min	Typ	Max		
R_{thJC}	Thermal Resistance, Junction to Case	-	-	0.3	$^\circ\text{C/W}$	
R_{thJA}	Thermal Resistance, Junction to Ambient	-	-	50		Leaded
T_{sold}	Soldering Temperature, Wave Soldering Only Allowed At Leads	-	-	260	$^\circ\text{C}$	1.6mm (0.063in.) from Case for 10s

Electrical Characteristics @ $T_j = 25^\circ\text{C}$, Unless Otherwise Specified

Static Characteristics						
$V_{(BR)DSS}$	Drain to Source Breakdown Voltage	600	640	-	V	$V_{GS} = 0\text{V}$, $I_D = 1\text{mA}$
$V_{GS(th)}$	Gate Threshold Voltage	2.1	3	3.9		$V_{DS} = V_{GS}$, $I_D = 250\mu\text{A}$
I_{DSS}	Zero Gate Voltage Drain Current	-	0.5	10	μA	$V_{DS} = 600\text{V}$, $V_{GS} = 0\text{V}$, $T_j = 25^\circ\text{C}$
		-	-	250		$V_{DS} = 600\text{V}$, $V_{GS} = 0\text{V}$, $T_j = 150^\circ\text{C}$
I_{GSS}	Gate Source Leakage Current	-	-	200	nA	$V_{GS} = \pm 20\text{V}$, $V_{DS} = 0\text{V}$
$R_{DS(on)}$	Drain to Source On-State Resistance	-	0.075	0.09	Ω	$V_{GS} = 10\text{V}$, $I_D = 18\text{A}$, $T_j = 25^\circ\text{C}$
		-	0.2	-		$V_{GS} = 10\text{V}$, $I_D = 18\text{A}$, $T_j = 150^\circ\text{C}$
R_{GS}	Gate Resistance	-	6	-	Ω	$f = 1\text{MHz}$, open drain

ICE35N60W


Symbol	Parameter	Values			Unit	Conditions
		Min	Typ	Max		
Dynamic Characteristics						
C _{iss}	Input Capacitance	-	5970	-	pF	V _{GS} = 0V, V _{DS} = 25V, f = 1 MHz
C _{oss}	Output Capacitance	-	677	-		
C _{rss}	Reverse Transfer Capacitance	-	35	-		
g _{fs}	Transconductance	-	30	-	S	V _{DS} = >2*I _D * R _{DS} , I _D = 15A
t _{d(on)}	Turn-on Delay Time	-	160	-	nS	V _{DS} = 380V, V _{GS} = 10V, I _D = 35A, R _G = 4Ω (External)
T _r	Rise Time	-	25	-		
t _{d(off)}	Turn-off Delay Time	-	20	-		
t _f	Fall Time	-	25	-		

Gate Charge Characteristics						
Q_{gs}	Gate to Source Charge	-	36	-	nC	$V_{DS} = 480V, I_D = 35A, V_{GS} = 0\text{ to }10V$
Q_{gd}	Gate to Drain Charge	-	62	-		
Q_g	Gate Charge Total	-	187	-		
$V_{plateau}$	Gate Plateau Voltage	-	5.3	-	V	


Reverse Diode						
V_{SD}	Diode Forward Voltage	-	0.95	1.2	V	$V_{GS} = 0V, I_S = I_F$
t_{rr}	Reverse Recovery Time	-	547	-	ns	$V_{RR} = 480V, I_S = I_F, d_{IF}/d_t = 100\text{ A}/\mu\text{S}$
Q_{rr}	Reverse Recovery Charge	-	12	-	μC	
I_{rm}	Peak Reverse Recovery Current	-	43	-	A	

ICE35N60W


Output Characteristics




Transfer Characteristics




On State Resistance vs Drain Current



On Resistance vs Junction Temperature




Gate Charge




ICE35N60W


Gate Threshold Voltage vs. Junction Temperature




Capacitance



Drain to Source Breakdown Voltage vs. Junction Temperature



Maximum Rate Forward Biased Safe Operating Area



Transient Thermal Response - Junction to Case

