

75 Ohm BNC Male Connector Crimp/Solder Attachment For RG59



TECHNICAL DATA SHEET

PE4602

75 Ohm BNC Male Connector Crimp/Solder Attachment For RG59

Configuration

ConnectorBNC MaleConnector Interface TypeRG59Cable Attachment Method (Shield/Contact)Crimp/SolderBody StyleStraight

Electrical Specifications

Frequency Range, MHz
Impedance, Ohms
75
Maximum VSWR
1.3:1
Maximum Operating Voltage, Volts
Dielectric Withstanding Voltage, Vrms
1,500

Mechanical Specifications

Temperature

Operating Range, deg C -65 to +165

Size

 Length, in [mm]
 1.132 [28.75]

 Width/Dia., in [mm]
 0.571 [15]

 Weight, lbs [g]
 0.027 [12.25]

Connector

Type BNC Male
Contact Material and Plating Brass, Gold
Contact Plating Specification 30μ in. minimum
Body Material and Plating Brass, Nickel
Body Plating Specification 100μ in. minimum

Dielectric Type Teflon

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant Yes

Plotted and Other Data

Notes: Values at 25 °C, sea level

URL: http://www.pasternack.com/bnc-male-standard-rg59-connector-pe4602-p.aspx

75 Ohm BNC Male Connector Crimp/Solder Attachment For RG59 from Pasternack Enterprises has same day shipment for domestic and International orders. We maintain 99% availability of the industry's broadest selection of RF, microwave and fiber optic products.

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.

ISO 9001 : 2008 Registered

PE4602 CAD Drawing

75 Ohm BNC Male Connector Crimp/Solder Attachment For RG59

