




Digital transistors (built-in resistors)

EMH11 General purpose transistor (dual transistors)


FEATURES

- Two DTC114E chips in a package
- Mounting possible with SOT-563 automatic mounting machines
- Transistor elements are independent, eliminating interference
- Mounting cost and area be cut in half

Marking: H11



SOT-563



Absolute maximum ratings(Ta=25°C)

Parameter	Symbol	Value		Unit
Supply voltage	V _{CC}	50		V
Input voltage	V _{IN}	-10~40		V
Output current	I _O	50		mA
	I _{C(MAX)}	100		
Power dissipation	P _d	150		mW
Junction temperature	T _j	150		°C
Storage temperature	T _{stg}	-55~+150		°C

Electrical characteristics (Ta=25°C)

Parameter	Symbol	Min.	Typ	Max.	Unit	Conditions
Input voltage	V _{I(off)}	0.5			V	V _{CC} =5V, I _O =100µA
	V _{I(on)}			3		V _O =0.3V, I _O =10mA
Output voltage	V _{O(on)}			0.3	V	I _O /I _I =10mA/0.5mA
Input current	I _I			0.88	mA	V _I =5V
Output current	I _{O(off)}			0.5	µA	V _{CC} =50V, V _I =0
DC current gain	G _I	30				V _O =5V, I _O =5mA
Input resistance	R ₁	7	10	13	kΩ	-
Resistance ratio	R ₂ /R ₁	0.8	1	1.2		-
Transition frequency	f _T		250		MHz	V _{CE} =10V, I _O =5mA, f=100MHz