


RECOMMENDED PCB LAYOUT



CIRCUIT: SPDT

CONTACT CONFIGURATION

SWITCH FUNCTION			
PDS. 1	PDS. 2	PDS. 3	
DN	NDNE	DN	
2-3	DPEN	2-1	

- NOTES:
1. ALL DIMENSIONS IN MM [IN]
  2. GENERAL TOLERANCE: 0.0=±0.4, 0.00=±0.25
  3. TERM. NOS. FOR REF ONLY
  4. CONTACT RATING: 5A @120VAC or 28VDC; 2A @250VAC
  5. ELECTRICAL LIFE: 50,000 MAKE AND BREAK AT FULL LOAD
  6. INSULATION RESISTANCE: 1,000 MEGA-OHM MIN
  7. DIELECTRIC STRENGTH: 1,000V RMS @SEA LEVEL
  8. OPERATION TEMP.: -30°C TO +85°C
  9. 2002/95/EC (ROHS) COMPLIANT.

REV.	ECN No.	DESCRIPTION	DATE	CHKD
C	18604	REVISE TERMINAL LENGTH DIMENSION	7/30/09	BLR
B	11115	REVISED & REDRAWN	12/13/00	PML
A	11025	RELEASED FOR PRODUCTION	10/25/00	PML

TITLE		E-SWITCH®		LAMB INDUSTRIES	
300 SP-1 R1 M2 Q E		DATE		DR	
SCALE		DATE		DWG	
2:1		7/30/09		PML	
				T311003	
				REV	
				C	

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED