

P-Channel Enhancement Mode MOSFET

Description

The WPM4801 is the Dual P-Channel logic enhancement mode power field effect transistors are produced using high cell density, DMOS trench technology.

This high density process is especially tailored to minimize on-state resistance.

These devices are particularly suited for low voltage application, notebook computer power management and other battery powered circuits where high-side switching.



Features

- -30V/-5.0A, $R_{DS(ON)} = 37m\Omega @ V_{GS} = -10V$
- -30V/-4.0A, $R_{DS(ON)} = 45m\Omega @ V_{GS} = -4.5V$
- Super high density cell design for extremely low $R_{DS(ON)}$
- Exceptional on-resistance and maximum DC current capability
- SOP – 8P package design

Application

- Power Management in Note book
- Portable Equipment
- Battery Powered System
- DC/DC Converter
- Load Switch
- DSC
- LCD Display inverter

PIN CONNECTIONS



WPM4801
YYWW

YYWW = Date Code

WPM4801 = Specific Device Code

Marking Diagram and explain

Order information

Part Number	Part Number	Shipping
WPM4801-8/TR	SOP-8P	2500Tape&Reel

Pin Assignment

Pin	Symbol	Description
1	S1	Source 1
2	G1	Gate 1
3	S2	Source 2
4	G2	Gate 2
5	D2	Drain 2
6	D2	Drain 2
7	D1	Drain 1
8	D1	Drain 1

Absolute Maximum Ratings

(T_A=25°C Unless otherwise noted)

Parameter		Symbol	Typical	Unit
Drain-Source Voltage		V _{DSS}	-30	V
Gate –Source Voltage		V _{GSS}	±12	V
Continuous Drain Current(T _J =150°C)	T _A =25°C	I _D	-5.6	A
	T _A =70°C		-4.5	
Pulsed Drain Current		I _{DM}	-30	A
Continuous Source Current(Diode Conduction)		I _S	-2.3	A
Power Dissipation	T _A =25°C	P _D	2.0	W
	T _A =70°C		1.2	
Operating Junction Temperature		T _J	-55/150	°C
Storage Temperature Range		T _{STG}	-55/150	°C
Thermal Resistance-Junction to Ambient		R _{θJA}	62.5	°C/W

Electrical Characteristics


(TA=25°C Unless otherwise noted)

Parameter	Symbol	Conditions	Min.	Typ	Max.	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-30			V
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.6	-1.0	-1.4	
Gate Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 12V$			± 100	nA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-24V, V_{GS}=0V$			-1	uA
		$V_{DS}=-24V, V_{GS}=0V$ $T_J=85^\circ C$			-10	
On-State Drain Current	$I_{D(on)}$	$V_{DS}=-5V, V_{GS}=-10V$	-25			A
Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=-10V, I_D=-5.0A$	0.030	0.037	0.050	Ω
		$V_{GS}=-4.5V, I_D=-4.0A$	0.036	0.045	0.060	
Forward Transconductance	g_{fs}	$V_{DS}=-5V, I_D=-4.3A$		12		S
Diode Forward Voltage	V_{SD}	$I_S=-1.0A, V_{GS}=0V$		-0.75	-1.5	V


Dynamic

Total Gate Charge	Q_g	$V_{DS}=-15V, V_{GS}=-10V$ $I_D=-4.3A$		10	15	nC
Gate-Source Charge	Q_{gs}			3.4		
Gate-Drain Charge	Q_{gd}			1.7		
Input Capacitance	C_{iss}	$V_{DS}=-15V, V_{GS}=0V$ $f=1MHz$		560		pF
Output Capacitance	C_{oss}			100		
Reverse Transfer Capacitance	C_{rss}			67		
Turn-On Time	$t_{d(on)}$	$V_{DD}=-15V, R_L=15\Omega$ $I_D=-1.0A, V_{GEN}=-10V$ $R_G=6\Omega$		7	15	nS
	t_r			10	20	
Turn-Off Time	$t_{d(off)}$			40	80	
	t_f			20	40	


Typical Characteristicis




Drain Current VS Drain-Source voltage



Drain Current VS Gate-Source Voltage




$R_{DS(on)}$ Resistance VS Gate-Source Voltage




Source Current VS Source to Drain Voltage


Typical Characteristics



Gate-source voltage vs Temperature






$R_{DS(on)}$ Resistance VS T_J Temperature







$R_{DS(on)}$ Resistance VS I_D , Drain Current

Typical Characteristics



Packaging Information



SYMBOLS	DIMENSIONS IN MILLIMETERS			DIMENSIONS IN INCHES		
	MIN	NOM	MAX	MIN	NOM	MAX
A	1.47	1.60	1.73	0.058	0.063	0.068
A1	0.10	—	0.25	0.004	—	0.010
A2	—	1.45	—	—	0.057	—
b	0.33	0.41	0.51	0.013	0.016	0.020
C	0.19	0.20	0.25	0.0075	0.008	0.0098
D	4.80	4.85	4.95	0.189	0.191	0.195
E	5.80	6.00	6.20	0.228	0.236	0.244
E1	3.80	3.90	4.00	0.150	0.154	0.157
e	—	1.27	—	—	0.050	—
L	0.38	0.71	1.27	0.015	0.028	0.050
Δy	—	—	0.076	—	—	0.003
θ	0°	—	8°	0°	—	8°