


- PARTMARKING DETAILS – BCX17
- COMPLIMENTARY TYPES - BCX19



### ● ABSOLUTE MAXIMUM RATINGS.

PARAMETER	SYMBOL	VALUE	UNIT
Collector-Emitter Voltage	$V_{CES}$	-50	V
Collector-Emitter Voltage ( $I_C = -10mA$ )	$V_{CEO}$	-45	V
Emitter-Base Voltage	$V_{EBO}$	-5	V
Collector Current	$I_C$	-500	mA
Peak Collector Current	$I_{CM}$	-1000	mA
Peak Emitter Current	$I_{EM}$	-1000	mA
Base Current	$I_B$	-100	mA
Peak Base Current	$I_{BM}$	-200	mA
Power Dissipation at $T_{amb}=25^\circ C$	$P_{tot}$	330	mW
Operating and Storage Temperature Range	$T_j:T_{stg}$	-55 to +150	$^\circ C$

### ● ELECTRICAL CHARACTERISTICS (at $T_{amb} = 25^\circ C$ unless otherwise stated).

PARAMETER	SYMBOL	MIN.	TYP.	MAX.	UNIT	CONDITIONS.
Collector-Base Cut-Off Current	$I_{CBO}$			-100 -200	nA $\mu A$	$I_E = 0, V_{CB} = -20V$ $I_E = 0, V_{CB} = -20V, T_j = 150^\circ C$
Emitter-Base Cut-Off Current	$I_{EBO}$			-10	$\mu A$	$I_C = 0, V_{EB} = -1V$
Base-Emitter Voltage	$V_{BE}$			-1.2	V	$I_C = -500mA, V_{CE} = -1V^*$
Collector-Emitter Saturation Voltage	$V_{CE(sat)}$			-620	mV	$I_C = -500mA, I_B = -50mA^*$
Static Forward Current Transfer Ratio	$h_{FE}$	100 70 40		600		$I_C = -100mA, V_{CE} = -1V$ $I_C = -300mA, V_{CE} = -1V^*$ $I_C = -500mA, V_{CE} = -1V^*$
Transition Frequency	$f_T$		100		MHz	$I_C = -10mA, V_{CE} = -5V$ $f = 35MHz$
Output Capacitance	$C_{obo}$		8.0		pF	$V_{CB} = -10V, f = 1MHz$

\*Measured under pulsed conditions.  
Spice parameter data is available upon request for this device

