


TX7-705-SQ-HP

High precision analogue temperature compensated
SMD TCXO



QuartzCom
the communications company



Features

- Applications: instrumentation, synchronisation, satellite navigation
- High frequency stability vs. temperature: $\pm 0.10 \sim \pm 0.5$ ppm
- Output signal Clipped sine wave or CMOS
- Low phase noise, high reliability

Standard frequencies	10, 12.2880, 12.8, 16.384, 20, 25, 30, 32, 32.768, 33.6, 40, 49.152 & 50 MHz		
Frequency range	5.0 ~ 52.0 MHz		
Frequency stability vs. temperature reference to $(F_{MAX}+F_{MIN})/2$	$\leq \pm 0.5$ ppm $\leq \pm 0.2$ ppm $\leq \pm 1.0$ ppm	over -40 to +85 °C over -40 to +85 °C over -55 to +95 °C	standard on request on request
vs. supply voltage changes reference to frequency at nominal supply	$\leq \pm 0.05$ ppm	± 5 %	
vs. load changes reference to frequency at nominal load	$\leq \pm 0.05$ ppm	± 10 %	
vs. aging	$\leq \pm 1.0$ ppm	1 st year	
Frequency slope	≤ 0.05 ppm/°C	over operating temperature	
G-sensitivity	< 1.5 ppb/g < 0.5 ppb/g	Gamma Γ Gamma Γ	standard on request
Short term stability (ADEV)	< 1×10^{-10}	$\tau = 1$ s	
Supply voltage (nominal value needs to be defined)	+2.7 V to +5.0 V	(2.7 V, 3.0 V, 3.3 V & 5.0 V)	
Supply current	1.5 ~ 8 mA	10 MHz ~ 52 MHz	
Output signal	Clipped sine wave	CMOS	
Output level	> 0.8 V _{p-p}	V _{OH} > 0.9 x V _{dc} / V _{OL} < 0.1 x V _{dc}	
Output load	10 k Ω // 10 pF	≤ 15 pF	
Symmetry (duty cycle)		45 / 55 % @ 1/2 V _{dc}	
Tri-state function	Input $\geq 0.7 \times V_{dc}$ or open Input $\leq 0.3 \times V_{dc}$ or GND	Output \rightarrow oscillation Output \rightarrow high impedance	
Phase noise @ 20.0 MHz	< -125 dBc/Hz < -145 dBc/Hz < -155 dBc/Hz < -155 dBc/Hz	@ 100 Hz @ 1 kHz @ 10 kHz @ 100 kHz	
Operating temperature range	-20 ~ +70 °C -40 ~ +85 °C -55 ~ +95 °C	indoor outdoor (extended temperature range on request)	
Storage temperature range	-55 ~ +125 °C		
Reflow Profiles as per IPC/JEDEC J-STD-020C	≤ 260 °C over 10 sec. Max.		
Moisture sensitivity	Level 1 (unlimited)		




Pin function


- # 1 GND or not connected
- # 5 GND
- # 6 Output
- # 9 NC or E/D
- # 10 V_{dc}

Do not connect #2, #3, #4, #7, #8

Test circuit (CSW)



Solder pattern



Specifications subject to change without notice

QuartzCom AG
Bischmattstrasse 11
CH 2544 Bettlach
Switzerland

0011/65/EU RoHS compliant

Fax +41 32 644 24 05
Tel +41 32 644 24 00
E-Mail sales@quartzcom.com
www.quartzcom.com

21 Feb. 15

