


Material:  
 Contact:  
 Phosphor Bronze thickness 0.15mm  
 Plating:  
 Contact Plating, Tin plated 60u"~80u"  
 Insulator:  
 PBT-4830, UL 94V-0

SPECIFICATIONS:  
 Current Rating: 1A  
 Dielectric withstanding Voltage: 1000v  
 RMS/minute  
 Insulator resistance: 5000 Megohms min.  
 Contact resistance: 20 milliohms initial  
 30 milliohms after test.  
 Operating temperatures: -55°C to 85°C  
 Insertion force: 340g (12 oz) max. per contact.  
 Withdrawal force: 80g (2.82 oz) min. per contact.

Dimensions

Positions	A	B	C	D
① 22	27.94	25.40	12.70	10.16

**RoHS compliant**  
 Unit: mm

Scale	FREE					Date	Name	Customer-No.
TOLERANCE						Drawn	29.07.2014	Amy
X.	±0.38					Approved	17.10.2014	Amy
X.X	±0.25							
X.XX	±0.13							
DIM	TOL	①	Update P/N to 22 pins version	17.10.2014	Ray	 ASSMANN WSW-No. ①A22-LC-T2 Drawing-No. ASS 6528 CO rev01 Replace Sheet		
Angle	±3°	②	Drawn	29.07.2014	Ray			
Angle	TOL	Id.	Modification	Date	Name			