

# SHINDENGEN

## Schottky Rectifiers (SBD)

Single

**D5S6M**

**60V 5A**


### FEATURES

- $T_j$ 150°C
- $P_{RRSM}$  avalanche guaranteed
- Fully Isolated Molding

### APPLICATION

- Switching power supply
- DC/DC converter
- Home Appliances, Office Equipment
- Telecommunication

### OUTLINE DIMENSIONS



### RATINGS

#### ● Absolute Maximum Ratings (If not specified $T_c$ =25°C)


Item	Symbol	Conditions	Ratings	Unit
Storage Temperature	$T_{stg}$		-55~150	°C
Operating Junction Temperature	$T_j$		150	°C
Maximum Reverse Voltage	$V_{RM}$		60	V
Repetitive Peak Surge Reverse Voltage	$V_{RRSM}$	Pulse width 0.5ms, duty1/40	65	V
Average Rectified Forward Current	$I_o$	50Hz sine wave, R-load, $T_c$ =130°C	5	A
Peak Surge Forward Current	$I_{FSM}$	50Hz sine wave, Non-repetitive 1 cycle peak value, $T_j$ =125°C	100	A
Repetitive Peak Surge Reverse Power	$P_{RRSM}$	Pulse width 10 μ s, $T_j$ = 25°C	330	W
Dielectric Strength	$V_{dis}$	Terminals to case, AC 1 minute	1.5	kV
Mounting Torque	$T_{OR}$	(Recommended torque: 0.3N·m)	0.5	N·m


#### ● Electrical Characteristics (If not specified $T_c$ =25°C)

Item	Symbol	Conditions	Ratings	Unit
Forward Voltage	$V_F$	$I_F$ =5A, Pulse measurement	Max 0.58	V
Reverse Current	$I_R$	$V_R$ = $V_{RM}$ , Pulse measurement	Max 4.5	mA
Junction Capacitance	$C_j$	f=1MHz, $V_R$ =10V	Typ 260	pF
Thermal Resistance	$\theta_{jc}$	junction to case	Max 4.5	°C/W
	$\theta_{jf}$	junction to heatsink (Reference value)	Max 6.0	

D5S6M


Forward Voltage






D5S6M

Reverse Current






D5S6M



Reverse Power Dissipation



$T_j = 150^\circ\text{C}$









D5S6M

Peak Surge Forward Capability



## SBD Repetitive Surge Reverse Power Derating Curve



## SBD Repetitive Surge Reverse Power Capability

