



SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
ON	OFF	ON
5-4	OPEN	5-6



- NOTE:
- ALL DIMENSIONS IN MM [INCH]
 - GENERAL TOLERANCE: X.X = ±0.4
X.XX = ±0.25
 - TERMINAL NUMBERS FOR REF ONLY
 - ▲ 4. STATIONARY CONTACTS: COPPER ALLOY W/ GOLD PLATING
 - ▲ 5. MOVING CONTACT: COPPER ALLOY W/ GOLD PLATING
 - RATING: 0.4 VA max. @ 20V AC OR DC max.
 - CONTACT RESISTANCE: <100 MILLI-OHM
 - MECHANICAL LIFE: 40,000 MAKE-AND-BREAK CYCLES.
 - INSULATION RESISTANCE: 500 MEGA-OHM min.
 - DIELECTRIC STRENGTH: 500 V RMS @SEA LEVEL.
 - OPERATING TEMP.: -30°C to 85°C
 - ▲ DENOTES CRITICAL PARAMETER.
 - SEAL RATING: IP67
 - 2002/95/EC (ROHS) COMPLIANT



A	22112	New-Release	1/6/16	MW
REV	PCR NO	DESCRIPTION	DATE	BY

TITLE 200USP3T1A1M2RE				
SCALE	DATE	DR	DWG	REV
2:1	1/6/2016	MW	T250011	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED