



BNC Male Connector Crimp/Non-Solder Contact
Attachment For LMR-400, PE-C400, LMR-400-DB

TECHNICAL DATA SHEET

EZ-400-BM-X

Configuration

Connector	BNC Male
Connector Interface Type	LMR-400,PE-C400,LMR-400-DB
Cable Attachment Method (Shield/Contact)	Crimp/Non-Solder Contact
Body Style	Straight

Electrical Specifications

Frequency Range, GHz	DC to 4
Impedance, Ohms	50
Maximum VSWR	1.35:1
Dielectric Withstanding Voltage, Vrms	1,500

Mechanical Specifications

Temperature

Operating Range, deg C	-55 to +155
------------------------	-------------

Size

Length, in [mm]	1.94 [49.28]
Width/Dia., in [mm]	0.62 [15.75]
Weight, lbs [g]	0.1 [45.36]

Connector

Type	BNC Male
Contact Material and Plating	Copper, Gold
Coupling Nut Material and Plating	Brass, Tri-Metal
Body Material and Plating	Brass, Tri-Metal
Dielectric Type	PTFE

Compliance Certifications (visit www.Pasternack.com for current document)

RoHS Compliant	Yes
----------------	-----

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-400, PE-C400, LMR-400-DB EZ-400-BM-X](#)

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.



BNC Male Connector Crimp/Non-Solder Contact
Attachment For LMR-400, PE-C400, LMR-400-DB

TECHNICAL DATA SHEET

EZ-400-BM-X

Plotted and Other Data

Notes:

Values at 25 °C, sea level
Non Solder Center Pin

BNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-400, PE-C400, LMR-400-DB from Pasternack Enterprises has same day shipment for domestic and International orders. Our RF, microwave and fiber optic products maintain a 99% availability and are part of the broadest selection in the industry.

Click the following link (or enter part number in "SEARCH" on website) to obtain additional part information including price, inventory and certifications: [BNC Male Connector Crimp/Non-Solder Contact Attachment For LMR-400, PE-C400, LMR-400-DB EZ-400-BM-X](#)

URL: <http://www.pasternack.com/bnc-male-standard-lmr-400-connector-ez-400-bm-x-p.aspx>

The information contained in this document is accurate to the best of our knowledge and representative of the part described herein. It may be necessary to make modifications to the part and/or the documentation of the part, in order to implement improvements. Pasternack reserves the right to make such changes as required. Unless otherwise stated, all specifications are nominal.