


## Schottky Diodes

### PD3S130L (KD3S130L)

#### ■ Features

- Ultra-Small Surface Mount Package
- Guard Ring Die Construction for Transient Protection
- High Surge Capability
- Lead Free Finish, RoHS Compliant



#### ■ Absolute Maximum Ratings Ta = 25°C

Parameter	Symbol	Rating	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>	30	V
Working Peak Reverse Voltage	V <sub>RWM</sub>		
DC Blocking Voltage	V <sub>R</sub>		
RMS Reverse Voltage	V <sub>R(RMS)</sub>	21	
Average Forward Current	I <sub>FAV</sub>	1	A
Non-Repetitive Peak Forward Surge Current @ 8.3mS	I <sub>FSM</sub>	22	
Thermal Resistance Junction to Ambient	R <sub>θ JA</sub>	177 (typ)	°C/W
Thermal Resistance Junction to Soldering Point	R <sub>θ JS</sub>	6	°C/W
Junction Temperature	T <sub>J</sub>	125	°C
Storage Temperature range	T <sub>stg</sub>	-55 to 150	

#### ■ Electrical Characteristics Ta = 25°C

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Reverse breakdown voltage	V <sub>R</sub>	I <sub>R</sub> = 1.5 mA	30			V
Forward voltage	V <sub>F1</sub>	I <sub>F</sub> = 100 mA			0.33	
	V <sub>F2</sub>	I <sub>F</sub> = 700 mA			0.37	
	V <sub>F3</sub>	I <sub>F</sub> = 1 A			0.42	
Reverse voltage leakage current	I <sub>R1</sub>	V <sub>R</sub> = 5 V			250	uA
	I <sub>R2</sub>	V <sub>R</sub> =30 V			1.5	mA
Junction capacitance	C <sub>j</sub>	V <sub>R</sub> =10 V, f= 1 MHz		40		pF

#### ■ Marking

Marking	31
---------	----

## Schottky Diodes

### PD3S130L (KD3S130L)

#### ■ Typical Characteristics




Fig. 1 Forward Power Dissipation




Fig. 2 Typical Forward Characteristics




Fig. 3 Typical Reverse Characteristics




Fig. 4 Total Capacitance vs. Reverse Voltage




Fig. 5 Forward Current Derating Curve




Fig. 6 Operating Temperature Derating