

FMV24N25G

FUJI POWER MOSFET

Super FAP-G series

N-CHANNEL SILICON POWER MOSFET


Features

- High speed switching
- Low on-resistance
- No secondary breakdown
- Low driving power
- Avalanche-proof


Applications

- Switching regulators
- UPS (Uninterruptible Power Supply)
- DC-DC converters

Outline Drawings [mm]



Equivalent circuit schematic



Maximum Ratings and Characteristics

Absolute Maximum Ratings at Tc=25°C (unless otherwise specified)

Description	Symbol	Characteristics	Unit	Remarks
Drain-Source Voltage	V _{DS}	250	V	
	V _{DSX}	220	V	V _{GS} = -30V
Continuous Drain Current	I _D	±24	A	
Pulsed Drain Current	I _{DP}	±96	A	
Gate-Source Voltage	V _{GS}	±30	V	
Repetitive and Non-Repetitive Maximum Avalanche Current	I _{AR}	24	A	Note*1
Non-Repetitive Maximum Avalanche Energy	E _{AS}	192	mJ	Note*2
Maximum Drain-Source dV/dt	dV _{DS} /dt	20	kV/μs	V _{DS} ≤ 200V
Peak Diode Recovery dV/dt	dV/dt	5	kV/μs	Note*3
Maximum Power Dissipation	P _D	2.16	W	T _a = 25°C
		65		T _c = 25°C
Operating and Storage Temperature range	T _{ch}	150	°C	
	T _{stg}	-55 to +150	°C	
Isolation	V _{ISO}	2	KVrms	t = 60sec, f = 60Hz

Electrical Characteristics at Tc=25°C (unless otherwise specified) Static Ratings

Description	Symbol	Conditions	min.	typ.	max.	Unit
Drain-Source Breakdown Voltage	BV _{DSS}	I _D = 250μA, V _{GS} = 0V	250	-	-	V
Gate Threshold Voltage	V _{GS} (th)	I _D = 250μA, V _{DS} = V _{GS}	3.0	-	5.0	V
Zero Gate Voltage Drain Current	I _{DSS}	V _{DS} = 250V, V _{GS} = 0V, T _{ch} = 25°C	-	-	25	μA
		V _{DS} = 200V, V _{GS} = 0V, T _{ch} = 125°C	-	-	250	
Gate-Source Leakage Current	I _{GSS}	V _{GS} = ±30V, V _{DS} = 0V	-	10	100	nA
Drain-Source On-State Resistance	R _{DS} (on)	I _D = 12A, V _{GS} = 10V	-	0.11	0.13	Ω
Forward Transconductance	g _{fs}	I _D = 12A, V _{DS} = 25V	8	16	-	S
Input Capacitance	C _{iss}	V _{DS} = 75V	-	1150	1725	pF
Output Capacitance	C _{oss}	V _{GS} = 0V	-	200	300	
Reverse Transfer Capacitance	C _{rss}	f = 1MHz	-	13	19.5	
Turn-On Time	td(on)	V _{CC} = 72V	-	27	40.5	ns
	tr	V _{GS} = 10V	-	22	33	
Turn-Off Time	td(off)	I _D = 12A	-	35	52.5	
	tf	R _G = 10Ω	-	14	21	
Total Gate Charge	Q _G	V _{CC} = 72V	-	36	54	nC
Gate-Source Charge	Q _{GS}	I _D = 24A	-	14.5	21.8	
Gate-Drain Charge	Q _{GD}	V _{GS} = 10V	-	11.5	17.3	
Avalanche Capability	I _{AV}	L = 560uH, T _{ch} = 25°C	24	-	-	A
Diode Forward On-Voltage	V _{SD}	I _F = 24A, V _{GS} = 0V, T _{ch} = 25°C	-	1.0	1.5	V
Reverse Recovery Time	trr	I _F = 24A, V _{GS} = 0V	-	0.23	-	μS
Reverse Recovery Charge	Q _{rr}	-di/dt = 100A/μs, T _{ch} = 25°C	-	2.5	-	μC







Thermal Characteristics







Description	Symbol	min.	typ.	max.	Unit
Channel to Case	R _{th} (ch-c)			1.923	°C/W
Channel to Ambient	R _{th} (ch-a)			58.0	°C/W



Note *1 : T_{ch} ≤ 150°C

Note *2 : Stating T_{ch} = 25°C, I_{AS} = A, L = 560uH, V_{CC} = 48V, R_G = 50Ω,
E_{AS} limited by maximum channel temperature and avalanche current.

Note *3 : I_F = I_D, -di/dt = 50A/μs, V_{CC} ≤ BV_{DSS}, T_{ch} ≤ 150°C.







WARNING

1. This Catalog contains the product specifications, characteristics, data, materials, and structures as of March 2010.
The contents are subject to change without notice for specification changes or other reasons. When using a product listed in this Catalog, be sure to obtain the latest specifications.
2. All applications described in this Catalog exemplify the use of Fuji's products for your reference only. No right or license, either express or implied, under any patent, copyright, trade secret or other intellectual property right owned by Fuji Electric Systems Co., Ltd. is (or shall be deemed) granted. Fuji Electric Systems Co., Ltd. makes no representation or warranty, whether express or implied, relating to the infringement or alleged infringement of other's intellectual property rights which may arise from the use of the applications described herein.
3. Although Fuji Electric Systems Co., Ltd. is enhancing product quality and reliability, a small percentage of semiconductor products may become faulty. When using Fuji Electric semiconductor products in your equipment, you are requested to take adequate safety measures to prevent the equipment from causing a physical injury, fire, or other problem if any of the products become faulty. It is recommended to make your design fail-safe, flame retardant, and free of malfunction.
4. The products introduced in this Catalog are intended for use in the following electronic and electrical equipment which has normal reliability requirements.

• Computers	• OA equipment	• Communications equipment (terminal devices)	• Measurement equipment
• Machine tools	• Audiovisual equipment	• Electrical home appliances	• Personal equipment
			• Industrial robots etc.
5. If you need to use a product in this Catalog for equipment requiring higher reliability than normal, such as for the equipment listed below, it is imperative to contact Fuji Electric Systems Co., Ltd. to obtain prior approval. When using these products for such equipment, take adequate measures such as a backup system to prevent the equipment from malfunctioning even if a Fuji's product incorporated in the equipment becomes faulty.

• Transportation equipment (mounted on cars and ships)	• Trunk communications equipment
• Traffic-signal control equipment	• Gas leakage detectors with an auto-shut-off feature
• Emergency equipment for responding to disasters and anti-burglary devices	• Safety devices
• Medical equipment	
6. Do not use products in this Catalog for the equipment requiring strict reliability such as the following and equivalents to strategic equipment (without limitation).

• Space equipment	• Aeronautic equipment	• Nuclear control equipment
• Submarine repeater equipment		
7. Copyright ©1996-2008 by Fuji Electric Systems Co., Ltd. All rights reserved.
No part of this Catalog may be reproduced in any form or by any means without the express permission of Fuji Electric Systems Co., Ltd.
8. If you have any question about any portion in this Catalog, ask Fuji Electric Systems Co., Ltd. or its sales agents before using the product.
Neither Fuji Electric Systems Co., Ltd. nor its agents shall be liable for any injury caused by any use of the products not in accordance with instructions set forth herein.