

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 19 BY -

ALL RIGHTS RESERVED.

LOC	DIST
1	-

REVISIONS

P	LTR	DESCRIPTION	DATE	DWN	APVD
	D2	DRAFTING CORRECTION	04SEP2012	A.B.	M.G.
	D3	ADDED ALTERNATIVE SHAPE VERSION	20MAR2016	M.P.	M.G.

FORMA ALTERANTIVA
(ALTERNATIVE SHAPE)

PARETE DIVISORIA
RIBASSATA
(SEPARATION WALL
LOWERED)

Dimensions: 27.8, 28.2, 41.5 REF.

Dimension: 28.5

Dimensions: 14.0 ± 0.2, 8.0 ± 0.2, 4.5 ± 0.2, 4.5 ± 0.2

Labels: A047, STE, PA66-GF13, 21, 2, 3, 4, 5

VERDE (GREEN)	PA 6.6 GF	D	284106-5
MARRONE (BROWN)		D	284106-4
ROSSO (RED)		D	284106-3
NERO (BLACK)		D	284106-2
NATURALE (NATURAL)		D	284106-1
COLORE (COLOUR)	MATERIALE (MATERIAL)	REV.	NUMERO (PART NUMBER)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN C. PIA 15JUN98

CHK A. GENTA 15JUN98

APVD A. BRUNI 15JUN98

PRODUCT SPEC 108-

APPLICATION SPEC 114-

WEIGHT -

CUSTOMER DRAWING

DIMENSIONS:
mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC	±0.3
1 PLC	±-
2 PLC	±-
3 PLC	±-
4 PLC	±-
ANGLES	±2
FINISH	SEE TABLE

MATERIAL SEE TABLE

FINISH SEE TABLE

WEIGHT -

CUSTOMER DRAWING

TE Connectivity

NAME
5 POS. MODULAR CONN FOR
MICRO-RELAY WITH SECONDARY LOCK

SIZE CAGE CODE DRAWING NO RESTRICTED TO

A300779 C-284106

SCALE 2:1 SHEET 1 OF 2 REV D3

1470-19 (3/11)

4

3

2

1

THIS DRAWING IS UNPUBLISHED.

RELEASED FOR PUBLICATION

20

© COPYRIGHT 19 BY -

ALL RIGHTS RESERVED.

LOC

DIST

REVISIONS

P

LTR

DESCRIPTION

DATE

DWN

APVD

SEE SHEET 1

ASOLE ADDIZIONALI PER ASSEMBLAGGIO MULTIPLO
(ADDITIONAL SLOTS FOR MULTIPLE MOUNTING)ASOLE PER ASSEMBLAGGIO SINGOLO
(SLOTS FOR SINGLE MOUNTING)

Sm. 0.3x45°

LATO INSERIZIONE
(INSERTION SIDE)

1.0±0.1

28.0

30.0

16.4

22.0^{+0.2}

13.3^{+0.2}

6.5

15.5

15.7^{+0.2}

24.7^{0.2}

52.0 MAX

55.0 MAX

26.0 REF.

26.0 REF.

RAPPRESENTAZIONE MODULARITA'
SCALA 1:1
NON ASSEMBLARE PIU' DI
2 CONNETTORI INSIEME
(SKETCH SHOWING CONNECTORS MODULARITY
SCALE 1:1
DO NOT ASSEMBLE MORE THAN
2 CONNECTORS TOGETHER)

DIMENSIONI RELAY
(RELAY DIMENSIONS)

4.5

4.5

14.0

8.0

4.8

6.3

11.3

3.3

PRELIMINARY

1

N°2 CAVITA' ADATTE PER TERMINALI STANDARD POWER TIMER P/N:
(N°2 CAVITIES SUITABLE FOR STANDARD POWER TIMER CONTACTS P/N:)
927829-5 FINISH: SILVERED, WIRE RANGE: 2.5-4.0 sqmm
(FINITURA: ARGENTATO, RANGO FILO: 2.5-4.0 sqmm)
1241818-5 FINISH: SILVERED, WIRE RANGE: 6.0 sqmm
(FINITURA: ARGENTATO, RANGO FILO: 6.0 sqmm)

2

N°3 CAVITA' ADATTE PER TERMINALI POSITIVE LOCK MARK II, .187 SERIES P/N:
(N°3 CAVITIES SUITABLE FOR POSITIVE LOCK MARK II, .187 SERIES CONTACTS P/N:)
173690-1 FINISH: PRE-TIN, WIRE RANGE: 0.35-0.5 sqmm
(FINITURA: PRE-STAGNATO, RANGO FILO: 0.35-0.5 sqmm)
173691-1 FINISH: PRE-TIN, WIRE RANGE: >0.5-1.0 sqmm
(FINITURA: PRE-STAGNATO, RANGO FILO: >0.50-1.0 sqmm)
1318306-1 FINISH: PRE-TIN, WIRE RANGE: >1.0-2.5 sqmm
(FINITURA: PRE-STAGNATO, RANGO FILO: >1.0-2.5 sqmm)

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN 15JUN98

C.PIA

15JUN98

CHK

A.GENTA

15JUN98

APVD

A.BRUNI

15JUN98

NAME

5 POS. MODULAR CONN FOR
MICRO-RELAY WITH SECONDARY LOCK

DIMENSIONS:

mm

TOLERANCES UNLESS
OTHERWISE SPECIFIED:

0 PLC ±0.3

1 PLC ±-

2 PLC ±-

3 PLC ±-

4 PLC ±-

ANGLES ±2

FINISH SEE TABLE

MATERIAL

SEE TABLE

SEE TABLE

15JUN98

15JUN98

15JUN98

108-

114-

-

-

-

-

-

-

-

-

STE

TE Connectivity

NAME

5 POS. MODULAR CONN FOR
MICRO-RELAY WITH SECONDARY LOCK

SIZE

A3

CAGE CODE

00779

DRAWING NO

C-284106

RESTRICTED TO

-

CUSTOMER DRAWING

SCALE

2:1

SHEET

2

OF

2

REV

D3

1470-19 (3/11)