AC Commom mode coil<Pin type:LF series> Sumida



LF2115

♦Outline

In addition to the standard versions of parameters shown here, custom designs are available to meet your exact requirements.


◆Application


TV, VCR, AV, OA equipment for noise prevention.

♦Features

- Small size and large inductance type.
- Excellent attenuation characteristics in low frequency range.
- **RoHS Compliance**


◆ Dimension (mm)







♦Circuit



- * Dimension does not include solder used on coil.
- *Terminal pitch is measured at the base(not from tip of the pin)

♦Specifications

Part No.	Stamp	Inductance [MIN.](mH) (1-2)(4-3) 1kHz	Inductance Balance [MAX.] (μ H)	D.C.R. (Ω) [MAX.](1-2)(4-3) (at 20℃)	Rated Current (50/60Hz) (Arms)※1
LF2115NP-222	222	2.2	150	0.24	1.3
LF2115NP-392	392	3.9	150	0.41	1.0
LF2115NP-103	103	10	550	1.00	0.6
LF2115NP-183	183	18	600	1.63	0.5
LF2115NP-223	223	22	800	2.04	0.4
LF2115NP-333	333	33	800	3.42	0.3

%1. Rated current: The AC current at which the temperature rise is $\Delta t = 45^{\circ}$ C.(Ta=20°C).

Note: This specification is subject to change without notice. Please contact your nearest sales office for updated information when placing an order.