

**isc N-Channel MOSFET Transistor**

**STD3NK60ZT4**

**• FEATURES**

- With TO-251(IPAK) packaging
- High speed switching
- Easy to use
- 100% avalanche tested
- Minimum Lot-to-Lot variations for robust device performance and reliable operation

**• APPLICATIONS**



- Power supply
- DC-DC converters
- Motor control
- Switching applications

**• ABSOLUTE MAXIMUM RATINGS(T<sub>a</sub>=25°C)**

SYMBOL	PARAMETER	VALUE	UNIT
V <sub>DSS</sub>	Drain-Source Voltage	600	V
V <sub>GSS</sub>	Gate-Source Voltage	±30	V
I <sub>D</sub>	Drain Current-Continuous	2.4 1.51	A
I <sub>DM</sub>	Drain Current-Single Pulsed	9.6	A
P <sub>D</sub>	Total Dissipation	45	W
T <sub>j</sub>	Operating Junction Temperature	-50~150	°C
T <sub>stg</sub>	Storage Temperature	-50~150	°C

**• THERMAL CHARACTERISTICS**

SYMBOL	PARAMETER	MAX	UNIT
R <sub>th(ch-c)</sub>	Channel-to-case thermal resistance	2.78	°C/W
R <sub>th(ch-a)</sub>	Channel-to-ambient thermal resistance	100	°C/W



**isc N-Channel MOSFET Transistor**

**STD3NK60ZT4**

**ELECTRICAL CHARACTERISTICS**

T<sub>C</sub>=25°C unless otherwise specified

SYMBOL	PARAMETER	CONDITIONS	MIN	TYP	MAX	UNIT
BV <sub>DSS</sub>	Drain-Source Breakdown Voltage	V <sub>GS</sub> =0V; I <sub>D</sub> = 1mA	600			V
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>DS</sub> =V <sub>GS</sub> ; I <sub>D</sub> =0.05mA	3.0		4.5	V
R <sub>DS(on)</sub>	Drain-Source On-Resistance	V <sub>GS</sub> = 10V; I <sub>D</sub> =1.2A		3.3	3.6	mΩ
I <sub>GSS</sub>	Gate-Source Leakage Current	V <sub>GS</sub> = ±20V; V <sub>DS</sub> = 0V			±0.1	μA
I <sub>DSS</sub>	Drain-Source Leakage Current	V <sub>DS</sub> = 600V; V <sub>GS</sub> = 0V; T <sub>J</sub> =25°C T <sub>J</sub> =125°C			1 50	μA
V <sub>SDF</sub>	Diode forward voltage	I <sub>SD</sub> =2.4A, V <sub>GS</sub> = 0 V			1.6	V