

## Tool - CF 1000-1,5 120V - 1208209

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Automatic stripping and crimping device, 120 V version, for insulated taped ferrules with a cross section range of 0.5-2.5 mm<sup>2</sup> in acc. with DIN 46228-4: 1990-09

### Why buy this product

- Rugged design
- Quick change of cross section without the need for additional adjustments
- Up to 1200 conductors can be processed an hour
- Suitable for bulk processing
- The pull-out forces meet the requirements of IEC/EN 60999 and IEC/EN 60947
- The stripping and crimping machine can be used to process loose ferrules with insulating collars according to DIN 46228-4
- Quantity counter
- The conductor is stripped in a single step and crimped with a ferrule to a high standard of quality

### Key commercial data

Packing unit	1
Minimum order quantity	1
Catalog page	Page 332 (CL2-2011)
GTIN	 4 046356 011358
Custom tariff number	84798100
Country of origin	GERMANY

### Technical data

#### General

Length (b)	490 mm
Height	390 mm
Width (a)	240 mm
Air consumption per compression	1.2 l
Working cycle	1.5 s
Weight	29 kg
Test standard	DIN 46228-4: 1990-09
Compression	trapezoidal

# Tool - CF 1000-1,5 120V - 1208209

## Classifications

### eclass

eCl@ss 4.0	21040301
eCl@ss 4.1	21040301
eCl@ss 5.0	21040301
eCl@ss 5.1	21040301
eCl@ss 6.0	17130101

### etim

ETIM 2.0	EC001186
ETIM 3.0	EC001186
ETIM 4.0	EC001186

### unspsc

UNSPSC 6.01	27112118
UNSPSC 7.0901	27111518
UNSPSC 11	23171604
UNSPSC 12.01	27111518
UNSPSC 13.2	27111518

## Accessories

### Accessories

### Tools

Conversion kit - CF 1000-TOOLKIT 0,34/ 6 - 1208212



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.25-0.34 mm<sup>2</sup>, AWG: 24-22, stripping length: 6 mm

Conversion kit - CF 1000-TOOLKIT 2,5/ 8 - 1208241



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.5-2.5 mm<sup>2</sup>, AWG: 20-14, stripping length: 8 mm

Conversion kit - CF 1000-TOOLKIT 4,0/10 - 1208270



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 4 mm<sup>2</sup>, AWG: 12, stripping length: 10 mm

## Tool - CF 1000-1,5 120V - 1208209

### Accessories

---

#### Conversion kit - CF 1000-TOOLKIT 0,34/ 8 - 1208225



Assembly set for CF 1000, for insulated taped ferrules according to DIN 46228-4: 1990-09, cross section range: 0.25-0.34 mm<sup>2</sup>, AWG: 24-22, stripping length: 8 mm

---

#### Spare knife - CF 1000 EM - 1205215

Accessories for CF 1000 stripping and crimping machine, replacement blade for 0.25 - 2.5 mm<sup>2</sup>, V-shaped

