




PIN	SYMBOL	PIN	SYMBOL
1	NC	11	C3+
2	V0	12	VOUT
3	V4	13	VSS
4	V3	14	VDD
5	V2	15	SE
6	V1	16	SCL
7	C2-	17	RS
8	C2+	18	/RES
9	C1+	19	/CS1
10	C1-	20	NC



- NOTES:
1. DISPLAY TYPE: FSTN
 2. VIEWING DIRECTION: 1200
 3. POLARIZER MODE: TRANSFLECTIVE/POSITIVE
 4. LOGIC VOLTAGE: 3.0V
 5. LCD OPERATING VOLTAGE: 9.0V
 6. DRIVE METHOD: 1/65 DUTY 1/9 BIAS
 7. OPERATING TEMP: 0°C~+50°C
 8. STORAGE TEMP: -20°C~+60°C
 9. CONTROLLER: S680724A01-BOCY
 10. BACKLIGHT: LED(WHITE)
 11. CONNECTOR: FPC
 12. LCD: TJCGS-0861
 13. UNMARKED TOLERANCES: ±0.3mm

TIAN-MA MICROELECTRONICS CO.
 6/F., CASTIC Building, Shennan Road, Central, Shenzhen, China

DRAWN BY: 文娟 24-03	TITLE: TM12864NCCUG1	
CHECKED BY: 罗超 24-03	DWG NO: G-1	
APPROVED BY: 罗超 24-03	SCALE: UNIT: mm	
CONFIRMED BY:	DWG NAME: TM12864NCCUG1-SHEET NO: 1 OF 1	