

MITSUBISHI HVIGBT MODULES  
**CM2400HC-34H**

3rd-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

HIGH POWER SWITCHING USE  
 INSULATED TYPE

**CM2400HC-34H**




- Ic ..... 2400A
- VCES ..... 1700V
- Insulated Type
- 1-element in a Pack
- AISiC Baseplate
- Soft Reverse Recovery Diode

**APPLICATION**

Traction drives, High Reliability Converters / Inverters, DC choppers

**OUTLINE DRAWING & CIRCUIT DIAGRAM**

Dimensions in mm



HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

Jul. 2005

**CM2400HC-34H**

**HIGH POWER SWITCHING USE  
INSULATED TYPE**

3rd-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

**MAXIMUM RATINGS**

Symbol	Item	Conditions	Ratings	Unit
V <sub>CE</sub> S	Collector-emitter voltage	V <sub>GE</sub> = 0V, T <sub>j</sub> = 25°C	1700	V
V <sub>GE</sub> S	Gate-emitter voltage	V <sub>CE</sub> = 0V, T <sub>j</sub> = 25°C	±20	V
I <sub>C</sub>	Collector current	T <sub>C</sub> = 80°C	2400	A
I <sub>CM</sub>		Pulse (Note 1)	4800	A
I <sub>E</sub> (Note 2)	Emitter current		2400	A
I <sub>EM</sub> (Note 2)		Pulse (Note 1)	4800	A
P <sub>C</sub> (Note 3)	Maximum power dissipation	T <sub>C</sub> = 25°C, IGBT part	17800	W
T <sub>j</sub>	Junction temperature		-40 ~ +150	°C
T <sub>op</sub>	Operating temperature		-40 ~ +125	°C
T <sub>stg</sub>	Storage temperature		-40 ~ +125	°C
V <sub>iso</sub>	Isolation voltage	RMS, sinusoidal, f = 60Hz, t = 1min.	4000	V
t <sub>p</sub> sc	Maximum short circuit pulse width	V <sub>CC</sub> = 1150V, V <sub>CE</sub> ≤ 1700V, V <sub>GE</sub> = 15V T <sub>j</sub> = 125°C	10	μs

**ELECTRICAL CHARACTERISTICS**

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
I <sub>CE</sub> S	Collector cut-off current	V <sub>CE</sub> = V <sub>CE</sub> S, V <sub>GE</sub> = 0V, T <sub>j</sub> = 25°C	—	—	36	mA
V <sub>GE(th)</sub>	Gate-emitter threshold voltage	I <sub>C</sub> = 240mA, V <sub>CE</sub> = 10V, T <sub>j</sub> = 25°C	4.5	5.5	6.5	V
I <sub>GE</sub> S	Gate leakage current	V <sub>GE</sub> = V <sub>GE</sub> S, V <sub>CE</sub> = 0V, T <sub>j</sub> = 25°C	—	—	0.5	μA
V <sub>CE(sat)</sub>	Collector-emitter saturation voltage	I <sub>C</sub> = 2400A, V <sub>GE</sub> = 15V, T <sub>j</sub> = 25°C (Note 4)	—	2.60	3.30	V
		I <sub>C</sub> = 2400A, V <sub>GE</sub> = 15V, T <sub>j</sub> = 125°C (Note 4)	—	3.10	—	
C <sub>ies</sub>	Input capacitance	V <sub>CE</sub> = 10V, f = 100kHz V <sub>GE</sub> = 0V, T <sub>j</sub> = 25°C	—	210	—	nF
C <sub>oes</sub>	Output capacitance		—	30.0	—	nF
C <sub>res</sub>	Reverse transfer capacitance		—	10.1	—	nF
Q <sub>g</sub>	Total gate charge	V <sub>CC</sub> = 850V, I <sub>C</sub> = 2400A, V <sub>GE</sub> = 15V, T <sub>j</sub> = 25°C	—	19.8	—	μC
V <sub>EC</sub> (Note 2)	Emitter-collector voltage	I <sub>E</sub> = 2400A, V <sub>GE</sub> = 0V, T <sub>j</sub> = 25°C (Note 4)	—	2.30	3.00	V
		I <sub>E</sub> = 2400A, V <sub>GE</sub> = 0V, T <sub>j</sub> = 125°C (Note 4)	—	1.85	—	
t <sub>d(on)</sub>	Turn-on delay time	V <sub>CC</sub> = 850V, I <sub>C</sub> = 2400A, V <sub>GE</sub> = ±15V R <sub>G(on)</sub> = 0.27Ω, T <sub>j</sub> = 125°C, L <sub>s</sub> = 80nH	—	—	1.60	μs
t <sub>r</sub>	Turn-on rise time		—	—	1.30	μs
E <sub>on</sub>	Turn-on switching energy	Inductive load	—	810	—	mJ/pulse
t <sub>d(off)</sub>	Turn-off delay time	V <sub>CC</sub> = 850V, I <sub>C</sub> = 2400A, V <sub>GE</sub> = ±15V R <sub>G(off)</sub> = 0.27Ω, T <sub>j</sub> = 125°C, L <sub>s</sub> = 80nH	—	—	2.70	μs
t <sub>f</sub>	Turn-off fall time		—	—	0.80	μs
E <sub>off</sub>	Turn-off switching energy	Inductive load	—	870	—	mJ/pulse
t <sub>rr</sub> (Note 2)	Reverse recovery time	V <sub>CC</sub> = 850V, I <sub>C</sub> = 2400A, V <sub>GE</sub> = ±15V	—	—	2.70	μs
Q <sub>rr</sub> (Note 2)	Reverse recovery charge	R <sub>G(on)</sub> = 0.27Ω, T <sub>j</sub> = 125°C, L <sub>s</sub> = 80nH	—	630	—	μC
E <sub>rec</sub> (Note 2)	Reverse recovery energy	Inductive load	—	330	—	mJ/pulse

- Note 1. Pulse width and repetition rate should be such that junction temperature (T<sub>j</sub>) does not exceed T<sub>opmax</sub> rating (125°C).  
 2. The symbols represent characteristics of the anti-parallel, emitter to collector free-wheel diode (FWDi).  
 3. Junction temperature (T<sub>j</sub>) should not exceed T<sub>jmax</sub> rating (150°C).  
 4. Pulse width and repetition rate should be such as to cause negligible temperature rise.

## CM2400HC-34H

HIGH POWER SWITCHING USE  
INSULATED TYPE

3rd-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

## THERMAL CHARACTERISTICS

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
R <sub>th(j-c)Q</sub>	Thermal resistance	Junction to Case, IGBT part	—	—	7.0	K/kW
R <sub>th(j-c)R</sub>		Junction to Case, FWDi part	—	—	12.0	K/kW
R <sub>th(c-f)</sub>	Contact thermal resistance	Case to Fin, $\lambda_{grease} = 1W/m \cdot K$	—	6.0	—	K/kW

## MECHANICAL CHARACTERISTICS

Symbol	Item	Conditions	Limits			Unit
			Min	Typ	Max	
M	Mounting torque	M8 : Main terminals screw	7.0	—	13.0	N·m
		M6 : Mounting screw	3.0	—	6.0	
		M4 : Auxiliary terminals screw	1.0	—	2.0	
—	Mass		—	1.5	—	kg
CTI	Comparative tracking index		600	—	—	—
d <sub>a</sub>	Clearance distance in air		19.5	—	—	mm
d <sub>s</sub>	Creepage distance along surface		32.0	—	—	mm
LC-E(int)	Internal inductance	IGBT part	—	10	—	nH


# CM2400HC-34H

HIGH POWER SWITCHING USE  
INSULATED TYPE


3rd-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules

## PERFORMANCE CURVES


**OUTPUT CHARACTERISTICS (TYPICAL)**




**TRANSFER CHARACTERISTICS (TYPICAL)**



**COLLECTOR-EMITTER SATURATION VOLTAGE CHARACTERISTICS (TYPICAL)**







**FREE-WHEEL DIODE FORWARD CHARACTERISTICS (TYPICAL)**



# CM2400HC-34H

HIGH POWER SWITCHING USE  
INSULATED TYPE

3rd-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules




**CM2400HC-34H**


**HIGH POWER SWITCHING USE  
INSULATED TYPE**

3rd-Version HVIGBT (High Voltage Insulated Gate Bipolar Transistor) Modules


**HALF-BRIDGE  
SWITCHING TIME CHARACTERISTICS  
(TYPICAL)**



**FREE-WHEEL DIODE  
REVERSE RECOVERY CHARACTERISTICS  
(TYPICAL)**



**TRANSIENT THERMAL  
IMPEDANCE CHARACTERISTICS**



**REVERSE BIAS SAFE OPERATING AREA  
(RBSOA)**

