



Micro Commercial Components
20736 Marilla Street Chatsworth
CA 91311
Phone: (818) 701-4933
Fax: (818) 701-4939

NTG Series

Features

- DO-35 glass package
- High stability
- Wide range of operating temperature from -50°C up to 250°C

High Accuracy NTC Thermistors

Applications


- Low cost probe assemblies
- High temperature printer ink sensing
- Consumer electronics
- High temperature – high speed tire manufacturing
- Printed circuit board temperature sensing
- Air-conditioner

General Characteristics

Symbol	Parameter	Value	Unit
R_{25}	Rated zero-power resistance	$10^2 \sim 10^6$	Ω
	Tolerance of R_{25}	$\pm 1\%, \pm 2\%, \pm 3\%, \pm 5\%, \pm 10\%$	
$B_{25/50}$ $B_{25/85}$	Range of B value	2000~5000	K
	Tolerance of B value	$\pm 0.5\%, \pm 1\%, \pm 1.5\%$	
	Dissipation factor*	≥ 2.0	mW
	Thermal time constant*	≤ 20	Sec.
	Rated power	250	mW
	Operating temperature range	-50 ~ +250	°C

* In still air

DO-35 GLASS



DIMENSIONS					
DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	---	.166	---	4.2	
B	---	.079	---	2.00	
C	---	.020	---	.52	
D	1.000	---	25.40	---	

NTG Series

Temperature	NTG 502-32XX	NTG 502-34XX	NTG 103-35XX	NTG 103-33XX	NTG 103-39XX	NTG 403-35XX	NTG 503-40XX	NTG 104-36XX	NTG 104-41XX	Package
°C	KΩ	KΩ	KΩ	KΩ	KΩ	KΩ	KΩ	KΩ	KΩ	
-50	154.5	208.6		329.2						DO-35G
40	88.85	112.86	249.6	188.4						
30	52.85	63.73	140.0	111.3	176.98					
20	32.43	37.40	80.36	67.74	97.10					
10	20.48	22.72	47.73	42.45	55.35					
0	13.29	14.23	29.37	27.28	32.67	115.0	167.1	301.3	340.9	
10	8.839	9.181	18.68	17.96	19.91	73.87	100.5	190.1	204.0	
20	6.013	6.086	12.24	12.09	12.50	48.77	62.61	123.1	125.9	
30	4.179	4.132	8.221	8.313	8.049	33.00	40.07	81.71	79.77	
40	2.962	2.869	5.648	5.828	5.314	22.82	26.28	55.40	51.82	
50	2.138	2.032	3.958	4.161	3.589	16.10	17.69	38.32	34.47	
60	1.568	1.467	2.823	3.021	2.478	11.57	12.13	27.01	23.42	
70	1.169	1.073	2.047	2.229	1.745	8.460	8.498	19.39	16.27	
80	0.8838	0.7959	1.506	1.669	1.252	6.281	6.051	14.15	11.52	
90	0.6774	0.5975	1.124	1.266	0.9117	4.732	4.390	10.49	8.305	
100	0.5267	0.4533	0.8502	0.9735	0.6739	3.613	3.226	7.870	6.092	
110	0.4130	0.3514	0.6510	0.7579	0.5064	2.793	2.409	5.971	4.524	
120	0.3276	0.2756	0.5046	0.5965	0.3858	2.183	1.821	4.583	3.411	
130	0.2631	0.2186	0.3956	0.4750	0.2974	1.728	1.395	3.553	2.603	
140	0.2131	0.1751	0.3137	0.3821	0.2321	1.379	1.081	2.784	2.008	
150	0.1742	0.1418	0.2515	0.3103	0.183	1.108	0.8473	2.202	1.569	
160						0.8948	0.6707	1.758	1.238	
170						0.7256	0.5364	1.417	0.9878	
180						0.5918	0.4331	1.151	0.7944	
190						0.4862		0.9423	0.6454	
200						0.4020		0.7774	0.5280	
210						0.3346		0.6452	0.4349	
220						0.2803		0.5406	0.3611	
230						0.2362		0.4553	0.3018	
240						0.2001		0.3857	0.2539	
250						0.1705		0.3288	0.2149	
260								0.2817	0.1831	
280										
300										
R ₂₅	5.00K	5.00K	10.00K	10.00K	10.00K	40.00K	50.00K	100.00K	100.00K	
B _{25/50}	3275	3470	3572	3380	3950	3508	4000	3697	4100	
B _{25/85}	3324	3528	3630	3435	3983	3550	4048	3750	4140	

Type No.

NTG

XXX

XXXX

X

①

②

③

④

① Series Name

② Resistance , for example :

502-----5kohm

103-----10kohm

403-----40kohm

503-----50kohm

104-----100kohm

③ Range of B Value, for example

3550-----3550K

3750-----3750K

④ Tolerance of R_{25} , for example:

1----- Tolerance of R_{25} is 1%

5----- Tolerance of R_{25} is 5%