

# Datasheet for 76650-0113

| General Information   |  |  |  |  |  |
|---|--|--|--|--|--|
| 76650-0113  |  |  |  |  |  |
| Molex / Waldom  |  |  |  |  |  |
| Micro-Latch Connector Kit   |  |  |  |  |  |
| Friction Lock Right Angle Header and Receptacle                         |  |  |  |  |  |
| Micro-Latch™  |  |  |  |  |  |
| (Molex Parts within this kit) - EU and China RoHS Compliant, UL and CSA |  |  |  |  |  |
| Kit assembled in U.S.A.   |  |  |  |  |  |
|   |  |  |  |  |  |

#### **Specifications**

| Design<br>Configuration: | Wire-to-Board                     |  |
|--------------------------|-----------------------------------|--|
| Pitch:                   | 2.00mm (.079")                    |  |
| Connector Type:          | ector Type: Receptacle and Header |  |
| Mounting<br>Orientation: | Right Angle                       |  |
| Circuit Sizes:           | 2, 3, 4, 6 and 8                  |  |
| Current Rating:          | (0.5 - 2) Amps depending on AWG   |  |
| Voltage:                 | 125 Volts                         |  |
| Wire size:               | 30-24 AWG                         |  |

## **Product Highlights**

Micro-Latch connectors provide a reliable connection interface for industry standard 2.00mm (.079") wire-to-board applications. The kit includes female crimp terminals, receptacle housings and semi-shrouded right angle headers. The connector applies a friction lock mechanism where the noses on the receptacle housings slide into the header wall openings. This ensures a durable mating and protection of the electrical circuits.

| Features and Benefits   | Applications  |
|---|---|
| <ul> <li>Uses popular terminals</li> <li>Friction lock for good mating retention</li> <li>Polarizing features ensures proper<br/>mating orientation</li> <li>Surface Mount Component vertical<br/>header is reflow process capable</li> </ul> | <ul> <li>Data Communication Equipment</li> <li>Printers/Faxes</li> <li>PC's and Monitors</li> <li>Automotive</li> <li>Home Entertainment</li> </ul> |



# Datasheet for 76650-0113

#### Bill of Materials for Part No. 76650-0113

| Molex Part No. | Country of Origin | Description   | Quantity in<br>Kit |
|----------------|-------------------|---|--------------------|
| 50212-8100     | Japan             | Micro-Latch™ Female Crimp Terminals 30-24 AWG                       | 100                |
| 51065-0200     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Receptacles, 2 Circuits           | 10                 |
| 51065-0300     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Receptacles, 3 Circuits           | 10                 |
| 51065-0400     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Receptacles, 4 Circuits           | 10                 |
| 51065-0600     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Receptacles, 6 Circuits           | 10                 |
| 51065-0800     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Receptacles, 8 Circuits           | 10                 |
| 53254-0270     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Right Angle Headers 2<br>Circuits | 10                 |
| 53254-0370     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Right Angle Headers 3<br>Circuits | 10                 |
| 53254-0470     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Right Angle Headers 4<br>Circuits | 10                 |
| 53254-0670     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Right Angle Headers 6<br>Circuits | 10                 |
| 53254-0870     | Malaysia          | 2.00mm (.079") Pitch Micro-Latch™ Right Angle Headers 8<br>Circuits | 10                 |

## Recommended Molex Tool(s) for Part No. 76650-0113\*

| Molex Part No. | Country of Origin | De              | escription |
|----------------|-------------------|-----------------|------------|
| 63819-0500 *   | Sweden            | Hand Crimp Tool |            |
| 57105-6000 *   | USA               | Extraction Tool |            |

\*Tools not included in kit. Tools ordered separately.