

PF08109B

MOS FET Power Amplifier Module for E-GSM and DCS1800 Dual Band Handy Phone

HITACHI

ADE-208-821B (Z)
3rd Edition
Mar. 2000

Application

- Dual band Amplifier for E-GSM (880 to 915 MHz) and DCS1800 (1710 to 1785 MHz)
- For 3.5 V nominal battery use

Features

- 2 in / 2 out dual band amplifire
- Simple external circuit including output matching circuit
- High gain 3stage amplifier : 0 dBm input Typ
- Lead less thin & Small package : 11 × 13.75 × 1.8 mm Typ
- High efficiency : 50% Typ at nominal output power for E-GSM
43% Typ at 32.7 dBm for DCS1800

Absolute Maximum Ratings (Tc = 25°C)

Item	Symbol	Rating	Unit
Supply voltage	Vdd	8	V
Supply current	I _{dd} _{GSM}	3	A
	I _{dd} _{DCS}	2	A
Vtxlo voltage	Vtxlo	4	V
Vapc voltage	Vapc	4	V
Input power	Pin	10	dBm
Operating case temperature	Tc (op)	-30 to +100	°C
Storage temperature	Tstg	-30 to +100	°C
Output power	Pout GSM	5	W
	Pout DCS	3	W

Note: The maximum ratings shall be valid over both the E-GSM-band (880 to 915 MHz), and the DCS1800-band (1710 to 1785 MHz).

Electrical Characteristics for DC (Tc = 25°C)

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Drain cutoff current	I _{ds}	—	—	100	μA	V _{dd} = 8 V, V _{apc} = 0 V
V _{apc} control current	I _{apc}	—	—	3	mA	V _{apc} = 2.2 V
V _{txlo} control current	I _{txlo}	—	—	100	μA	V _{txlo} = 2.4 V

Electrical Characteristics for E-GSM mode (Tc = 25°C)

Test conditions unless otherwise noted:

f = 880 to 915 MHz, V_{dd GSM} = 3.5 V, Pin_{GSM} = 0 dBm, R_g = R_l = 50 Ω, T_c = 25°C, V_{apc DCS} = 0.1 V

Pulse operation with pulse width 577 μs and duty cycle 1:8 shall be used.

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Frequency range	f	880	—	915	MHz	
Total efficiency (Hi)	η _{T(Hi)}	41	50	—	%	P _{out GSM} = 35.5dBm, V _{txlo} = 0.1V,
2nd harmonic distortion	2nd H.D.	—	-45	-38	dBc	V _{apc GSM} = controlled
3rd harmonic distortion	3rd H.D.	—	-45	-40	dBc	
Input VSWR	VSWR (in)	—	1.5	3	—	
Total efficiency (Lo)	η _{T(Lo)}	27	35	—	%	P _{out GSM} = 30.8dBm, V _{txlo} = 2.4V, V _{apc GSM} = controlled
Output power (1)(Hi)	P _{out (1)(Hi)}	35.5	36.0	—	dBm	V _{apc GSM} = 2.2V, V _{txlo} = 0.1V
Output power (1)(Lo)	P _{out (1)(Lo)}	30.8	31.3	—	dBm	V _{apc GSM} = 2.2V, V _{txlo} = 2.4V
Output power (2)(Hi)	P _{out (2)(Hi)}	33.5	34.0	—	dBm	V _{dd GSM} = 3.0V, V _{apc GSM} = 2.2V, T _c = +85°C, V _{txlo} = 0.1V
Output power (2)(Lo)	P _{out (2)(Lo)}	28.8	29.3	—	dBm	V _{dd GSM} = 3.0V, V _{apc GSM} = 2.2V, T _c = +85°C, V _{txlo} = 2.4V
Isolation	—	—	-42	-36	dBm	V _{apc GSM} = 0.2V, V _{txlo} = 0.1V
Isolation at DCS RF-output when GSM is active	—	—	-23	-17	dBm	P _{out GSM} = 35.5dBm, V _{txlo} = 0.1V Measured at f = 1760 to 1830MHz
Switching time	t _r , t _f	—	1	2	μs	P _{out GSM} = 0 to 35.5dBm, V _{txlo} = 0.1V
Stability	—	No parasitic oscillation			—	V _{dd GSM} = 3.0 to 5.1V, P _{out GSM} ≤ 35.5dBm, V _{txlo} = 0.1, 2.4V, V _{apc GSM} ≤ 2.2V, GSM pulse. R _g = 50Ω, Output VSWR = 6 : 1 All phases
Load VSWR tolerance	—	No degradation			—	V _{dd GSM} = 3.0 to 5.1V, t = 20sec., P _{out GSM} ≤ 35.5dBm, V _{txlo} = 0.1, 2.4V, V _{apc GSM} ≤ 2.2V, GSM pulse. R _g = 50Ω, Output VSWR = 10 : 1 All phases

Electrical Characteristics for DCS1800 mode (Tc = 25°C)




Test conditions unless otherwise noted:

f = 1710 to 1785 MHz, Vdd_{DCS} = 3.5 V, Pin_{DCS} = 0 dBm, Rg = Rl = 50 Ω, Tc = 25°C, Vapc_{GSM} = 0.1 V
 Pulse operation with pulse width 577 μs and duty cycle 1:8 shall be used.

Item	Symbol	Min	Typ	Max	Unit	Test Condition
Frequency range	f	1710	—	1785	MHz	
Total efficiency (Hi)	$\eta_{T(Hi)}$	36	43	—	%	Pout _{DCS} = 32.7dBm,
2nd harmonic distortion	2nd H.D.	—	-45	-38	dBc	Vapc _{DCS} = controlled
3rd harmonic distortion	3rd H.D.	—	-45	-40	dBc	
Input VSWR	VSWR (in)	—	1.5	3	—	
Total efficiency (Lo)	$\eta_{T(Lo)}$	17	25	—	%	Pout _{DCS} = 26.7dBm, Vapc _{DCS} = controlled
Output power (1)	Pout (1)	32.7	33.2	—	dBm	Vapc _{DCS} = 2.2V,
Output power (2)	Pout (2)	30.7	31.2	—	dBm	Vdd _{DCS} = 3.0V, Vapc _{DCS} = 2.2V, Tc = +85°C
Isolation	—	—	-42	-36	dBm	Vapc _{DCS} = 0.2V
Isolation at GSM RF-output when DCS is active	—	—	-10	0	dBm	Pout _{DCS} = 32.7dBm, Measured at f = 1710 to 1785MHz
Switching time	t _r , t _f	—	1	2	μs	Pout _{DCS} = 0 to 32.7dBm
Stability	—	No parasitic oscillation			—	Vdd _{DCS} = 3.0 to 5.1V, Pout _{DCS} ≤ 32.7dBm, Vapc _{DCS} ≤ 2.2V, DCS pulse. Rg = 50Ω, Output VSWR = 6 : 1 All phases
Load VSWR tolerance	—	No degradation			—	Vdd _{DCS} = 3.0 to 5.1V, Pout _{DCS} ≤ 32.7dBm, t = 20sec., Vapc _{DCS} ≤ 2.2V, DCS pulse. Rg = 50Ω, Output VSWR = 10 : 1 All phases

Package Dimensions

Unit: mm



Hitachi Code	RF-O-12
JEDEC	—
EIAJ	—
Mass (reference value)	—

Cautions

1. Hitachi neither warrants nor grants licenses of any rights of Hitachi's or any third party's patent, copyright, trademark, or other intellectual property rights for information contained in this document. Hitachi bears no responsibility for problems that may arise with third party's rights, including intellectual property rights, in connection with use of the information contained in this document.
2. Products and product specifications may be subject to change without notice. Confirm that you have received the latest product standards or specifications before final design, purchase or use.
3. Hitachi makes every attempt to ensure that its products are of high quality and reliability. However, contact Hitachi's sales office before using the product in an application that demands especially high quality and reliability or where its failure or malfunction may directly threaten human life or cause risk of bodily injury, such as aerospace, aeronautics, nuclear power, combustion control, transportation, traffic, safety equipment or medical equipment for life support.
4. Design your application so that the product is used within the ranges guaranteed by Hitachi particularly for maximum rating, operating supply voltage range, heat radiation characteristics, installation conditions and other characteristics. Hitachi bears no responsibility for failure or damage when used beyond the guaranteed ranges. Even within the guaranteed ranges, consider normally foreseeable failure rates or failure modes in semiconductor devices and employ systemic measures such as fail-safes, so that the equipment incorporating Hitachi product does not cause bodily injury, fire or other consequential damage due to operation of the Hitachi product.
5. This product is not designed to be radiation resistant.
6. No one is permitted to reproduce or duplicate, in any form, the whole or part of this document without written approval from Hitachi.
7. Contact Hitachi's sales office for any questions regarding this document or Hitachi semiconductor products.

HITACHI

Hitachi, Ltd.

Semiconductor & Integrated Circuits.
Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
Tel: Tokyo (03) 3270-2111 Fax: (03) 3270-5109

URL NorthAmerica : <http://semiconductor.hitachi.com/>
 Europe : <http://www.hitachi-eu.com/hel/ecg>
 Asia : <http://www.hitachi.com.sg/grp3/sicd>
 Japan : <http://www.hitachi.co.jp/Sicd/indx.htm>

For further information write to:

Hitachi Semiconductor
(America) Inc.
179 East Tasman Drive,
San Jose, CA 95134
Tel: <1> (408) 433-1990
Fax: <1>(408) 433-0223

Hitachi Europe GmbH
Electronic Components Group
Dornacher StraÙe 3
D-85622 Feldkirchen, Munich
Germany
Tel: <49> (89) 9 9180-0
Fax: <49> (89) 9 29 30 00

Hitachi Europe Ltd.
Electronic Components Group.
Whitebrook Park
Lower Cookham Road
Maidenhead
Berkshire SL6 8YA, United Kingdom
Tel: <44> (1628) 585000
Fax: <44> (1628) 585160

Hitachi Asia Ltd.
16 Collyer Quay #20-00
Hitachi Tower
Singapore 049318
Tel: 535-2100
Fax: 535-1533

Hitachi Asia Ltd.
Taipei Branch Office
3rd Flr, Hung Kuo Building, No.167,
Tun Hwa North Road, Taipei (105)
Taiwan
Tel: <886> (2) 2718-3666
Fax: <886> (2) 2718-8180
Telex: 23222 HAS-TP

Hitachi Asia (Hong Kong) Ltd.
Group III (Electronic Components)
7th Flr, North Tower, World Finance Centre,
Harbour City, Canton Road, Tsim Sha Tsui,
Kowloon, Hong Kong
Tel: <852> (2) 735 9218
Fax: <852> (2) 730 0281
Telex: 40815 HITEC HX

Copyright ' Hitachi, Ltd., 2000. All rights reserved. Printed in Japan.
Colophon 1.0

HITACHI