

| Product SKU:         | C2103.21           |
|----------------------|--------------------|
| Product Description: | Hook-Up<br>Premium |
| Product Category:    | Electronic         |

C2103.21.05 Hook-Up Wire, UL 1015, CSA TEW, Gauge Size (AWG): 18, Conductor/Strands: 16/30, Jacket: Premium Grade PVC, Temperature Range: -20°C to +105°C - Yellow - 1000 Ft. Spool Electronics - Hook-Up Wire - UL 1015, CSA TEW - STRANDED CONDUCTORS - Yellow



## **Product Construction:**

Conductor:

- 24 thru 10 AWG
- Fully-annealed, tinned copper per ASTM B-33
- Solid or stranded

Insulation:

- Color Code: See chart below
- Premium grade color-coded PVC
- Temperature range: -20 $\hat{A}^{\circ}C$  to +105 $\hat{A}^{\circ}C$

## **Product Specification:**

| Conductor Size (AWG):              | • 18          |
|------------------------------------|---------------|
| Conductor/Strands:                 | • 16/30       |
| No. of Pairs:                      | • 1           |
| Jacket Color:                      | • Yellow      |
| Nominal Insulation Thickness (in): | • 0.032       |
| Nominal Insulation Thickness (mm): | • 0.81        |
| Nominal Outside Diameter (in):     | • 0.112       |
| Nominal Outside Diameter (mm):     | • 2.84        |
| Standard Packaging:                | • 1000' Spool |

| Standard Package Quantity:  | • 1  |
|-----------------------------|--|
| UPC #:                      | • 079407768455   |
| Put-up:                     | • 1000   |
| SCC-14:                     | • 50079407768455   |
| Cube:                       | • 333.27   |
| Weight Per Unit of Measure: | • .01  |
| ColorOption:                | • Yellow   |
| Product Information:        |  |
| Applications:               | • Internal wiring of electrical and electronic equipment |
|                             | • Internal wiring of panels and meters                   |
|                             | • Point-to-point wiring                                  |
|                             | • Suggested voltage rating: 600 Volts                    |
| Compliances:                | • CSA Type TEW   |
|                             | • Designed to Meet UL VW-1 Vertical Wire Flame Test      |
|                             | • UL Style 1015 - 105°C, 600V                            |
| Packaging:                  | • 10,000 foot (3048m) Reels                              |
|                             | • 1000' (305 m) Spools                                   |
|                             | • Other put-ups available- consult Customer Service      |
| Reference Charts            |  |
| Color Code Chart            |  |
| Technical Specifications    |  |

<u>Unit Conversion Factors</u> <u>Cable Design Equations - Balanced Pair</u> <u>Insulation and Jacket Properties</u> <u>Temperature Conversion Chart</u> <u>Decimal and Unit Conversion Factors</u> <u>Cable Design Equations - Braid Shield</u> <u>AWG Conductor Chart</u> <u>Conduit Capacity Chart</u> Cable Design Equations - Coaxial Cable Engineering Prefixes Coax Connector Cross Reference Glossary





Designed to Meet UL VW-1 Vertical Wire Flame Test Underwriters Laboratories Inc.

