

## Interactive Catalog Replaces Catalog Pages

Honeywell Sensing and Control has replaced the PDF product catalog with the new **Interactive Catalog**. The **Interactive Catalog** is a power search tool that makes it easier to find product information. It includes more installation, application, and technical information than ever before.



**Click this icon to try the new  
Interactive Catalog.**

---

**Sensing and Control**  
Honeywell Inc.  
11 West Spring Street  
Freeport, Illinois 61032



# Pressure Sensors

## Gage/Unamplified-Noncompensated

22PC Series

### Basic Sensors



### FEATURES

- Lowest priced pressure sensor
- Miniature package
- Can be used to measure with vacuum or positive pressure
- Operable after exposure to frozen conditions
- 2 mA constant current excitation significantly reduces sensitivity shift over temperature\*

### 22PC SERIES PERFORMANCE CHARACTERISTICS at 10.0 ±0.01 VDC Excitation, 25°C

	Min.	Typ.	Max.	Units
Excitation	---	10	12	VDC
Null Shift, 25° to 0°, 25° to 50°C	---	±2.0	---	mV
Null Offset	-30	0	+30	mV
Linearity, P2 > P1, BFSL	---	±0.25	±1.0	%Span
Span Shift, 25° to 0°, 25° to 50°C	---	±6.0	---	%Span
Repeatability & Hysteresis	---	±0.15	---	%Span
Response Time	---	---	1.0	msec
Input Resistance	4.0 K	5.0 K	6.0 K	ohms
Output Resistance	4.0 K	5.0 K	6.0 K	ohms
Weight	---	2	---	grams

### ENVIRONMENTAL SPECIFICATIONS

Operating Temperature	-40° to +85°C (-40° to +185°F)
Storage Temperature	-55° to +100°C (-67° to +212°F)
Shock	Qualification tested to 150 g
Vibration	Qualification tested to 0 to 2 kHz, 20 g sine
Media (P1 & P2)	Limited only to those media which will not attack polyetherimide, silicon, fluorosilicone, silicone, EPDM, and neoprene seals

### 22PC SERIES ORDER GUIDE

Catalog Listing	Pressure Range psi	Span, mV			Sensitivity mV/psi Typ.	Overpressure psi, Max.
		Min.	Typ.	Max.		
22PCA Type	1.0	25	42	59	42	20
22PCC Type	15	156	225	294	15	45
22PCF Type	100	147	225	303	2.3	200

### SENSOR SELECTION GUIDE

2 Product Family	2 Circuit Type	PC Pressure Transducer	A Pressure Range	F Type of Seal	A Type of Port	6 Termination Style	G Pressure Measurement
2 20PC Family	2 Noncompensated low cost		A 1 psi C 15 psi F 100 psi	E EPDM F Fluorosilicone N Neoprene S Silicone	A Straight B Barbed D Modular J Needle	2 2 x 2 6 1 x 4 (.600")	G Gage

#### Example: 22PCAFA6G

Non-compensated low cost 1 psi sensor with fluorosilicone seal, straight port, 1 x 4 termination and gage pressure measurement.

See Accessory Guide, page 27.

**Note: Not all catalog listings are established. Please refer to the Order Guides, or contact the MICRO SWITCH Application Center at the 800 number.**

\* Non-compensated pressure sensors, excited by constant current instead of voltage, exhibit temperature compensation of Span. Application Note #1 briefly discusses current excitation.

Constant current excitation has an additional benefit of temperature measurement. When driven by a constant current source, a silicon pressure sensor's terminal voltage will rise with increased temperature. The rise in voltage not only compensates the Span, but is also an indication of die temperature.

### Constant Current Excitation Schematic

