



orange 1	green 2
white/orange	white/green
blue 3	brown 4
white/blue	white/brown

**Material:**

- Conductor:
  - Bare Copper
  - FTP STR 26AWG\*4P
- Insulator:
  - Thickness Min. at any point: 0.15MM
  - Thickness Max. Avg.: 0.25MM
  - Diameter: 0.85±0.06MM
- Jacket PVC:
  - Thickness Min. at any point: 0.50MM
  - Thickness Max. Avg.: 0.60MM
  - Diameter: 5.6±0.02MM

PA/R	PINOUT		
	P1(T568B)	WIRE	P2(T568B)
1	1	WHT/ORG	1
	2	ORG	2
2	3	WHT/GRN	3
	6	GRN	6
3	4	BLU	4
	5	WHT/BLU	5
4	7	WHT/BRN	7
	8	BRN	8

Ⓜ = Assmann logo



ITEM NO.

**A-MCSP-80050/R-R**

TITLE Cat.5e FTP Patch Cable - Red, 5 Meters, 8P8C, Twisted Pair, Foil Shielded

**ASSMANN**  
Electronics, Inc.

1840 W. Drake Drive, Suite 101 • Tempe, AZ 85283  
Toll Free: 1-877-277-6266 • Email: info@usa-assmann.com

THIS DRAWING IS UNPUBLISHED  
©Copyright 2010 by Assmann Electronic Components  
All International Rights Reserved