

Power Supplies - PS/2 Type

PS300-XP2

Model Name	P/N: 50903724000E						
PS200-1U ATX 200W	Input Range	Slide Switch (115Vac/230Vac)					
	Output Voltage	+5V	+3.3V	+12V	-12V	-5V	+5sb
		30/21.5A (0.5A min)	15/28A (0.3A min)	15A (4.2A min)	0.8A (0.4A min)	0.3A (0.15A)	2A (1A min)
	MTBF (hours)	AT 25°C 100,000h					
	Safety	TUV, CSA22.2 NO.60950-1, IEC, UL, NEMKO+CB, CE, 3C					
	Dimensions	150 x 140 x 74 mm					
	Compatible with Axiomtek Products	AX61221/AX61222/AX60501/AX60551/AX61400/ AX60552/AX6145/AX6156LE/AX61492					



Overview

Embedded
Systems

Embedded
Systems for
Transportation

Embedded
Field
Controllers

Embedded
MicroBoxes

Industrial
Barebone
Systems

Industrial
Chassis

Backplanes

PS301-XP2

Model Name	P/N: 50914734000E						
PS301-XP2 PS/2 Type ATX 300W	Input Range	90 – 264Vac Full Range					
	Output Voltage	+5V	+3.3V	+12V	-12V	-5V	+5Vsb
		30A (0.1A min)	28A (0.3A min)	15A	0.8A	0.3A	2A
	MTBF (hours)	AT 25°C 100,000h					
	Safety	TUV, CSA22.2 NO.60950-1, IEC, UL, NEMKO EN60950-1, CE, 3C					
	Dimensions	150 x 140 x 74 mm					
	Compatible with Axiomtek Products	AX61221/AX61222/AX60501/AX60551/AX60552/AX61400/ AX6145/AX6156LE/AX61492					



Power
Supplies

Peripherals &
Accessories

PS400-XP2

Model Name	P/N: 50904B24000E						
PS400-XP2 PS/2 Type ATX 400W	Input Range	90 – 264Vac Full Range					
	Output Voltage	+5V	+3.3V	+12V1	+12V2	-12V	+5Vsb
		20A (0.5A min)	20A (0.3A min)	16A (1A min)	16A (1A min)	0.5A	2.5A (1A min)
	MTBF (hours)	AT 25°C 100,000h					
	Safety	TUV, CSA22.2 NO.60950-1, IEC, UL, NEMKO+CB,CE					
	Dimensions	150 x 140 x 74 mm					
	Compatible with Axiomtek Products	AX61221/AX61222/AX60501/AX60551/AX60552/AX61400/ AX6145/AX6156LE/AX61492					



Power Supplies - PS/2 Type

PS500-XP2

Model Name	P/N: 50904C06000E							
PS500-XP2 PS/2 Type ATX 500W	Input Range	90 ~ 265VAC Full Range						
	Output Voltage	+5V	+3.3V	+12V	+12V1	+12V2	-12V	+5Vsb
		24A (0.3A min)	24A (0.5A min)	34A (1A min)	17A (1A min)	17A (1A min)	0.8A	2.5A
	MTBF (hours)	AT 25°C 100,000h						
	Safety	TUV, CUL, CB, IEC60950-1, GB4943-2001, UL60950-1, EN60950-1						
	Dimensions	150 x 140 x 86 mm						
Compatible with Axiomtek Products	AX61221/AX61222/AX60501/AX60551/AX60552/AX61400/ AX6145/AX6156LE/AX61492							

