



Micro Commercial Components

Micro Commercial Components 20736 Marilla Street Chatsworth CA 91311 Phone: (818) 701-4933 Fax: (818) 701-4939

### **Features**


- Small package saves board space
- Peak pulse current(tp=8/20us): 6A
- Low leakage
- ESD protection to over 8kV contact discharge
- For space saving application
- Can handle multiple ESD strikes
- Epoxy meets UL 94 V-0 flammability rating
- Moisture Sensitivity Level 1

## **Maximum Ratings**

• Operating Junction & Storage Temperature: -55°C to +150°C

Parameter		Symbol	Limits	unit
IEC61000-4-2(ESD)	Air		±15	
	Contact		±8	KV
IEC61000-4-4 (EFT): @ 5/50ns			40	Α

# **PinConfiguration**



#### **SOT-363** lв DIMENSIONS INCHES мм NOTE DIM MIN .006 MA> MIN MA> .014 0.15 0.3 В .045 .053 1.15 1.35 C .081 .096 2.05 2.45 D 0.65 minal .047 .071 .055 G 1.20 1.40 Н .087 1.80 2.20 .004 0.10 .035 0.90 .043 1.10 .018 .010 0.26 0.46 М .006 0.08 0.15

**SRV05-4** 

**5 Volts** 

**ESD** Protection

**Device** 

www.mccsemi.com



Parameter Symbol Conditions Min. Тур. Max. Units 5 V Reverse stand-off voltage  $V_{\text{RWM}}$ Pin 5 to 2  $I_t = 1mA$  (Pin 5 to 2) V Reverse Breakdown voltage  $V_{\mathsf{BR}}$ 6 V<sub>RWM</sub> = 5V T=25°C (Pin 5 to 2) Reverse Leakage Current  $\mathbf{I}_{\mathsf{R}}$ 2 μΑ I<sub>PP</sub>=1A t<sub>P</sub> = 8/20μ S **Clamping Voltage** Vc 15 V (Any Pin to 2)  $V_R=0V$  f = 1MHz Junction Capacitance  $\mathbf{C}_{j}$ 2.0 pF (Any I/O pin to pin 2) V<sub>R</sub>=0V f = 1MHz 1.0 pF (Between I/O pins)

Electrical characteristics per line@25°C(unless otherwise specified)

# www.mccsemi.com



### **Ordering Information :**

Device	Packing	
Part Number-TP	Tape&Reel: 3Kpcs/Reel	

### **\*\*\*IMPORTANT NOTICE\*\*\***

*Micro Commercial Components Corp.* reserves the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. *Micro Commercial Components Corp*. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold *Micro Commercial Components Corp*. and all the companies whose products are represented on our website, harmless against all damages.

### \*\*\*LIFE SUPPORT\*\*\*

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

### \*\*\*CUSTOMER AWARENESS\*\*\*

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

# www.mccsemi.com