

[Home](#) > [Products](#) > > [952911](#) > [952911BF](#)
[Add to myIDT \[?\]](#)

You may also like...


952911BF

Category:
Generic Part: 952911

Market Group: PC CLOCK

Description: PC MAIN CLOCK

ICS952911 is a 48 pin clock chip for VIA PT890 style chipsets. When used with a fanout DDR buffer, such as the 93788, it provides all the necessary clock signals for such a system. Output Features: $\hat{a}\hat{e}\hat{c}$ 2 - 0.7V current-mode differential CPU pairs $\hat{a}\hat{e}\hat{c}$ 10 - PCI, 3 free running, 33MHz $\hat{a}\hat{e}\hat{c}$ 3 - REF, 14.318MHz $\hat{a}\hat{e}\hat{c}$ 3 - 3V66, 66.66MHz $\hat{a}\hat{e}\hat{c}$ 1 - 48MHz $\hat{a}\hat{e}\hat{c}$ 1 - 24/48MHz $\hat{a}\hat{e}\hat{c}$ 2 - 25MHz @ 2.5V



Parameters

Package	SSOP 48 (PV48)
Speed	NA
Temperature	C
Voltage	3.3 V
Status	Active
Sample	Yes
Minimum Order Quantity	120
Factory Order Increment	30

Distributor Inventory

No Pricing information is available from our Distributors at this time.

Documents

Type	Title	Size	Revision Date
Misc	PC Clocks Contact Info	61 KB	05/29/2007

Package

Description	SSOP 300 MIL, 48LD
Class	PLASTIC
Moisture Sensitivity Level (MSL)	1
Category	Standard
Moisture Exposure Floor Life	Unlimited @ <30°C/85% RH
Peak Reflow Temperature	225°C
Rebake Conditions	NA
Length	15.9
Mark	F
Width	7.5
Pitch	0.64
Thickness	2.3
Status	Active