

# 7 outlet, 6-ft cord, 1080 joule strip - Protect It! Surge Suppressor

#### MODEL NUMBER: STRIKER



#### **Highlights**

- 7 outlets/6-ft. cord
- 1080 joule surge suppression rating
- \$20,000 Ultimate Lifetime
  Insurance (USA & Canada only)

#### **Applications**

 Ideal for any desktop, network or home computing application requiring AC line surge protection.

#### Package Includes

- STRIKER Surge Suppressor
- Instruction manual with warranty information

#### Description

Tripp Lite's STRIKER offers economical AC surge suppression for protection of workstations, desktop PCs, telecom systems and other sensitive electronics. AC surge suppression shields connected equipment from damage and performance problems due to transient surges. STRIKER offers 7 AC outlets, 6-ft. cord and diagnostic LEDs to warn of wiring problems and suppressor damage. AC suppression rated at 1080 joules shields equipment from surges and line noise. Attractive gray housing with keyhole mounting tabs and 1 designated transformer plug outlet offer convenient protection of desktop computer equipment and accessories. \$20,000 Ultimate Lifetime Insurance (USA & Canada only).

PLUG/OUTLETS: Input: NEMA5-15P/Output: 7 x NEMA5-15R/6-ft. AC line cord ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA5-15R wall receptacle)

FORMAT: Corded multi-outlet strip with 1 transformer-spaced outlet

SUPPRESSION: AC: 150V RMS Clamping/1080 joules/400V UL1449 Let-through Rating

#### **Features**

- 7 outlets
- 6-ft. cord
- Surge suppression rating: 1080 joules
- EMI/RFI noise filtering
- Can accommodate 1 transformer without blocking remaining outlets
- · Diagnostic LED indicate protection present
- . Keyhole supports for wall mounting
- \$20,000 Ultimate Lifetime Insurance (USA and Canada Only) covers connected equipment

### **Specifications**

**OVERVIEW** 





| Intended Application               | Home/Office  |  |
|------------------------------------|--|--|
| ОИТРИТ                             |  |  |
| Frequency compatibility            | 50 / 60 Hz   |  |
| Output watts                       | 1800   |  |
| Circuit Breaker (amps)             | 15   |  |
| Outlet quantity / type             | 7 NEMA 5-15R   |  |
| Transformer accommodation          | Supports 1 large transformer plug accessory without covering remaining outlets; accepts up to 4 transformers total |  |
| Outlet orientation                 | Single row   |  |
| INPUT                              |  |  |
| Nominal Input Voltage(s) Supported | 120V AC  |  |
| Recommended Electrical Service     | 120V (110-125V)  |  |
| Input connection type              | NEMA 5-15P   |  |
| Input cord length (ft.)            | 6  |  |
| Input cord length (m)              | 1.83   |  |
| Input cord gauge, type             | 14 gauge, SJT  |  |
| Voltage compatibility (VAC)        | 120  |  |
| Maximum Surge Amps                 | 72000  |  |
| UPC ASSIGNMENT                     |  |  |
| Unit Carton UPC#                   | 037332010520   |  |
| LEDS ALARMS & SWITCHES             |  |  |
| Switches                           | Combination AC circuit breaker and 2-position red illuminated on/off power switch                                  |  |
| Diagnostic LEDs                    | Built-in LED confirms suppressor "protection present" (green) status   |  |
| SURGE / NOISE SUPPRESSION          |  |  |
| AC suppression joule rating        | 1080   |  |
| AC suppression response time       | < 1 ns   |  |
| Protection modes                   | Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression                                 |  |
| Clamping voltage (RMS)             | 150  |  |
| UL1449 let through rating          | 400V   |  |
| EMI / RFI filtering                | Up to 20 dB  |  |
| DATALINE SURGE SUPPRESSION         |  |  |
| Cable (Coax) Protection            | No   |  |





| Network (Ethernet) Protection                              | No  |
|--|---|
| PHYSICAL   |   |
| Shipping Dimensions (HWD/in)                               | 13.78 x 4.52 x 1.77   |
| Shipping Dimensions (HWD/cm)                               | 35.00 x 11.48 x 4.50  |
| Shipping weight (lbs)                                      | 1.30  |
| Shipping weight (kg)                                       | 0.59  |
| Unit Dimensions (HWD/in)                                   | 1.32 x 2.05 x 11.69   |
| Unit Dimensions (HWD/cm)                                   | 3.35 x 5.21 x 29.69   |
| Unit weight (lbs)  | 1.17  |
| Unit weight (kg)   | 0.53  |
| Material of construction                                   | Plastic   |
| Integrated keyhole mounting tabs                           | Keyhole mounting tabs enable wall mounting  |
| Housing Color  | Light Gray  |
| Receptacle Color   | Light Gray  |
| AC line cord color   | Light Gray  |
| Style  | Strip   |
| Outlets center to center measurement                       | Distance between standard outlets = 29mm; Distance between last standard outlet and transformer outlet = 33mm |
| Keyhole slot center to center measurement                  | Distance between slots = 151mm; Distance between slot height = 24mm   |
| CERTIFICATIONS   |   |
| UL1449 3rd Edition (AC<br>Suppression)                     | UL1449 3rd Edition  |
| NOM (Mexico)   | NOM   |
| UL1363 (Power Tap)   | UL1363  |
| cUL / CSA (Canada)   | cUL   |
| Approvals  | Exceeds IEEE 587 category A&B specifications  |
| WARRANTY   |   |
| Product Warranty Period (Worldwide)                        | Lifetime limited warranty   |
| Connected Equipment Insurance (U.S., Canada & Puerto Rico) | \$20,000 Ultimate Lifetime Insurance  |

© 2014 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Tripp Lite: