


PARAMETERS		SYMBOL	MAX	MIN	TYP.	UNITS
POWER DISSIPATION	P_d	100	--	--		mW
FORWARD VOLTAGE	V_f	2.8	1.9	2.2		V
REVERSE VOLTAGE	V_r	5				V
EMISSION WAVELENGTH	λ_p			570		nm
AVE. FORWARD CURRENT	I_{af}	30	--			mA
LUMINOUS INTENSITY	I_v		6.0			mcad



CIRCUIT: SPDT
CONTACT CONFIGURATION

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 3. TERM. NO. FOR REF. ONLY
 4. RATING: 12mA @24V
 5. FIXED CONTACT/MOVING CONTACT:
COPPER ALLOY W/GOLD PLATE
 6. CONTACT BOUNCE: <5m SEC.
 7. CONTACT RESISTANCE: <50milli-OHMS

E-SWITCH®

REV.	ECN No.	DESCRIPTION	DATE	CHKD
A	11908	RELEASED FOR PRODUCTION	2/5/02	CJB

TITLE	SCALE	DATE	DR	DWG	REV
5500 STD BODY 2	2:1	2/5/02	CJB	R010010	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED