

Small Signal Product

200mW, Surface Mount Zener SMD Zener Diode

FEATURES

- Wide zener voltage range selection : 2.4V to 75V
- Surface Mount Device type
- Moisture sensitivity level 1
- Pb free and RoHS compliant
- Green compound (Halogen free) with suffix "G" on packing code and prefix "G" on date code
- Matte Tin(Sn) lead finish with Nickel(Ni) underplate



SOD-523F




MECHANICAL DATA

- Case: SOD-523F small outline plastic package
- Terminal: Matte tin plated, lead free, solderable per MIL-STD-202, Method 208 guaranteed
- High temperature soldering guaranteed: 260°C/10s
- Polarity: Indicated by cathode band
- Weight: 1.68 ± 0.5mg

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)			
PARAMETER	SYMBOL	VALUE	UNIT
Power Dissipation	P _D	200	mW
Forward Voltage	V _F	1	V
Thermal Resistance (Junction to Ambient)	R _{θJA}	625	°C/W
Junction and Storage Temperature Range	T _{STG}	-65 to +150	°C

Note1: Valid provided that electrodes are kept at ambient temperature

Zener I vs. V Characteristics



- V_{BR} : Voltage at I_{ZK}
- I_{ZK} : Test current for voltage V_{BR}
- Z_{ZK} : Dynamic impedance at I_{ZK}
- I_{ZT} : Test current for voltage V_Z
- V_Z : Voltage at current I
- Z_{ZT} : Dynamic impedance at I_{ZT}
- I_{ZM} : Maximum steady state current
- V_{ZM} : Voltage at I_{ZM}

Small Signal Product
Electrical Characteristics

 (Ratings at $T_A=25^{\circ}\text{C}$ ambient temperature unless otherwise specified)

Part Number	Marking	Zener Voltage Range			Maximum Zener Impedance			Maximum Reverse Current		
		$V_Z @ I_{ZT}$ (V)			I_{ZT} (mA)	$Z_{ZT} @ I_{ZT}$ (Ω)	I_{ZK} (mA)	$Z_{ZK} @ I_{ZK}$ (Ω)	$I_R @ V_R$ (μA)	V_R (V)
		Min	Nom	Max						
BZT52C2V0	RD	1.8	2.0	2.15	5	100	-	-	120	0.5
BZT52C2V2	RE	2.08	2.2	2.33	5	100	-	-	120	0.7
BZT52C2V4	Z7	2.2	2.4	2.6	5	100	1	1000	120	1
BZT52C2V7	A8	2.5	2.7	2.9	5	100	1	1000	120	1
BZT52C3V0	B8	2.8	3	3.2	5	100	1	1000	50	1
BZT52C3V3	C8	3.1	3.3	3.5	5	95	1	1000	20	1
BZT52C3V6	D8	3.4	3.6	3.8	5	90	1	1000	10	1
BZT52C3V9	E8	3.7	3.9	4.1	5	90	1	1000	5	1
BZT52C4V3	F8	4	4.3	4.6	5	90	1	1000	5	1
BZT52C4V7	G8	4.4	4.7	5	5	80	1	800	2	1
BZT52C5V1	H8	4.8	5.1	5.4	5	60	1	500	2	1.5
BZT52C5V6	I8	5.2	5.6	6	5	40	1	200	1	2.5
BZT52C6V2	J8	5.8	6.2	6.6	5	10	1	100	1	3
BZT52C6V8	K8	6.4	6.8	7.2	5	15	1	160	0.5	3.5
BZT52C7V5	L8	7	7.5	7.9	5	15	1	160	0.5	4
BZT52C8V2	M8	7.7	8.2	8.7	5	15	1	160	0.5	5
BZT52C9V1	N8	8.5	9.1	9.6	5	15	1	160	0.5	6
BZT52C10K	O8	9.4	10	10.6	5	20	1	160	0.1	7
BZT52C11K	P8	10.4	11	11.6	5	20	1	160	0.1	8
BZT52C12K	Q8	11.4	12	12.7	5	25	1	80	0.1	9
BZT52C13K	R8	12.4	13	14.1	5	30	1	80	0.1	10
BZT52C15K	S8	14.3	15	15.8	5	30	1	80	0.1	11
BZT52C16K	T8	15.3	16	17.1	5	40	1	80	0.1	12
BZT52C18K	U8	16.8	18	19.1	5	45	1	80	0.1	13
BZT52C20K	V8	18.8	20	21.2	5	55	1	100	0.1	15
BZT52C22K	W8	20.8	22	23.3	5	55	1	100	0.1	17
BZT52C24K	X8	22.8	24	25.6	5	70	1	120	0.1	19
BZT52C27K	Y8	25.1	27	28.9	5	80	1	300	0.1	21
BZT52C30K	Z8	28	30	32	5	80	1	300	0.1	23
BZT52C33K	A9	31	33	35	5	80	1	300	0.1	25
BZT52C36K	B9	34	36	38	5	90	1	500	0.1	27
BZT52C39K	C9	37	39	41	5	130	1	500	2	30
BZT52C43K	D9	40	43	46	5	150	1	500	2	33
BZT52C47K	E9	44	47	50	5	170	1	500	2	36
BZT52C51K	F9	48	51	54	5	180	1	500	1	39
BZT52C56K	G9	52	56	60	5	200	1	500	1	43
BZT52C62K	H9	58	62	66	5	215	1	500	0.2	47
BZT52C68K	I9	64	68	72	5	240	1	500	0.2	52
BZT52C75K	J9	70	75	79	5	255	1	500	0.2	57

 Notes : 1. The Zener Voltage (V_Z) is tested under pulse condition of 20ms.

 2. The device numbers listed have a standard tolerance on the nominal zener voltage of $\pm 2\%$.

 3. For detailed information on price, availability and delivery of nominal zener voltages between the voltages shown and tighter voltage tolerances, contact your nearest **Taiwan Semiconductor** representative.


 4. The zener impedance is derived from the 60-cycle ac voltage, which results when an ac current having an RMS value equal to 10% of the dc zener current (I_{ZT} or I_{ZK}) is superimposed to I_{ZT} or I_{ZK} .

Small Signal Product

RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

Fig. 1 Derating curve



Small Signal Product

ORDERING INFORMATION					
PART NO.	MANUFACTURE CODE	PACKING CODE	GREEN COMPOUND	PACKAGE	PACKING
BZT52CxxxK (Note1)	(Note 2)	RK	G	SOD-523F	3K / 7" Reel
		RS	G	SOD-523F	8K / 7" Reel


Note 1: "xxx" is Device Code from "2V0" thru "75"

Note 2: Manufacture special control, if empty means no special control requirement

EXAMPLE					
PREFERRED P/N	PART NO.	MANUFACTURE CODE	PACKING CODE	GREEN COMPOUND CODE	DESCRIPTION
BZT52C2V0K RSG	BZT52C2V0K		RS	G	Green compound
BZT52C2V0K -L0 RSG	BZT52C2V0K	L0	RS	G	Green compound


Small Signal Product

PACKAGE OUTLINE DIMENSIONS



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	0.70	0.90	0.028	0.035
B	1.50	1.70	0.059	0.067
C	0.25	0.40	0.010	0.016
D	1.10	1.30	0.043	0.051
E	0.50	0.77	0.020	0.030
F	0.07	0.20	0.003	0.008

SUGGESTED PAD LAYOUT



DIM.	Unit (mm)	Unit (inch)
	Typ.	Typ.
X	0.60	0.024
X1	2.30	0.091
Y	0.80	0.031

Small Signal Product**Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.