

FEATURES

- High Efficiency & Long Life
- Worldwide Input Range
- Compact Size
- Optimized Performance
- Fully Isolated & SELV
- Protections: Short Circuit/ Open Circuit/ Over Voltage/ Over Temperature
- Class 2 power unit



PRODUCT HIGHLIGHT

Output Voltage/Current Max 48V/350mA
:

SPECIFICATION

Model Name	FSP015-DZ48CE(035)	
Wattage	17W	
Dimming	Non-Dimming	
Input Electrical Specification	Input Voltage	200~240 Vac
	Input Frequency	47~63 Hz
	PFC	≥0.9
Constant Current / Constant Voltage	Constant Current	
Output Voltage and Current Rating	Output1	36-48 V , 350 mA
Output Electrical Specification	Efficiency	≥ 80 %
	Life	50,000 hours without system & full load.@230Vac Vac & ambient 40°C
	Protection Function	OVP,OTP,SCP,OCB
Environmental Requirement	TEMP. Range	Operating : 0°C to +40°C Storage : -20°C to +60°C
	Insulation	Primary to Secondary: 500Vdc,25M ohms min.
EMC performance	EN55015	Class B Conducted, Class B radiated
	EN55022	Class B Conducted, Class B radiated
	EN61000-3-2	A
	EN61000-4-3	1
Dimension	78.5mm(L) x 51.8mm(W)x 31.5mm(H)	

PROTECTION FUNCTIONS

OVP,OTP,SCP,OCB

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice